

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW01					
ILTOJ (IF/IAF)		EWIVO (FB)		008.45 / 6.00				1600		CLIMB TO 3000 DIRECT UFEMI AND HOLD, CONTINUE CLIMB-IN-HOLD TO 3000.					
EWIVO (FAF)		HALVA/1.50 NM TO RW01 (FB)		008.45 / 2.94											
HALVA/1.50 NM TO RW01		RW01 (MAP) (FO)		008.45 / 1.50											
RW01 (MAP)		322 MSL		008.45											
322 MSL		UFEMI (FO)						3000		ADDITIONAL FLIGHT DATA: HOLD N, RT, 188.45 INBOUND. CHART FAS OBST: 174 TREE 361559N/0770947W DISTANCE TO THLD FROM 255 HAT: 0.64 NM. WAAS CHANNEL # 70637 REFERENCE PATH ID: W01A CHART CIRCLING ICON. LTP HAE: -14.7 M					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)															
2. HOLD S ILTOJ, RT, 008.45 INBOUND, 3000 FT. IN LIEU OF PT (IAF)															
3. FAC: 008.45 FAF: EWIVO DIST FAF TO MAP: 4.44 THLD: 4.44															
4. MIN. ALT: ILTOJ 3000, EWIVO 1600, HALVA/1.50 NM TO RW01 600*															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: 1600 GS ALT AT: EWIVO 1600 OM: _____ MM: _____ IM: _____															
7. GS ANGLE: 3.17 TCH: 40.9 34:1 IS NOT CLEAR															
8. MSA FROM: _____															
MAG VAR: 10W EPOCH YEAR: 2000															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @			
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	359	1	292	359	1	292	359	1	292		NA				
LNAV/VNAV DA	322	1	255	322	1	255	322	1	255		NA				
LNAV MDA	440	1	373	440	1	373	440	1	373	440	1	373			
CIRCLING															
	580	1	513	580	1	513	580	1 1/2	513	820	2 1/2	753			
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: NIGHT LANDING: RWY 1 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE FRANKLIN ALTIMETER SETTING AND INCREASE ALL DA 67 FEET AND ALL MDA 80 FEET; INCREASE LPV ALL CATS VISIBILITY 1/8 MILE, LNAV CATS C/D (SEE FORM 8260-10)															
CITY AND STATE AHOSKIE, NC		ELEVATION: 67 TDZE: 67 AIRPORT NAME: TRI-COUNTY		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 30 APRIL 2015						SUP: AMDT: NONE			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

VISIBILITY 3/8 MILE AND CIRCLING CAT D VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV NA WHEN USING FRANKLIN ALTIMETER SETTING.

CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C(5F) OR ABOVE 54C(130F).

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

* LNAV ONLY.

TAA

	FROM	TO	ALT
1.	278/30 CW 098/30 (NOPT)	ILTOJ (IF/IAF) (FB)	3000
2.	098/30 CW 278/30	ILTOJ (IF/IAF) (FO)	3000



CITY AND STATE

AHOSKIE, NC

ELEVATION: 67

TDZE: 67

AIRPORT NAME:

TRI-COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 1, ORIG

30 APRIL 2015

SUP:

AMDT: **NONE**

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KASJ
RUNWAY	RW01
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W01A
LTP/FTP LATITUDE	361728.8475N
LTP/FTP LONGITUDE	0771014.3270W
LTP/FTP ELLIPSOIDAL HEIGHT	-00147
FPAP LATITUDE	361858.0395N
FPAP LONGITUDE	0771017.3100W
THRESHOLD CROSSING HEIGHT (TCH)	00040.9
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.17
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1384
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 96A43F3E

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00203
FPAP ORTHOMETRIC HEIGHT	+00203

QUALITY
16
CHECKED

CITY AND STATE AHOSKIE, NC	ELEVATION: 67 TDZE: 67 AIRPORT NAME: TRI-COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 30 APRIL 2015	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KASJK7FR01	AILTOJ	010ILTOJK7EA0EE	AR	HF		00850040	+	03000	18000		A	JS
SUSAP	KASJK7FR01	R	010ILTOJK7EA0E	I	IF			+	03000	18000		A	JS
SUSAP	KASJK7FR01	R	020EWIVOK7EA1E	F	051TF		00850060	+	01600			A	JS
SUSAP	KASJK7FR01	R	020EWIVOK7EA2WALPV			ALNAV/VNAV						JS	
SUSAP	KASJK7FR01	R	021HALVAK7EA0E	S	031TF		00850029	V	0060000612	-317		A	JS
SUSAP	KASJK7FR01	R	030RW01	K7PG0GY	M	031TF	00850015		00108	-317		A	JS
SUSAP	KASJK7FR01	R	040		0	M	0085	+	00322			A	JS
SUSAP	KASJK7FR01	R	050UFEMIK7EA0EY		DF			+	03000			A	JS
SUSAP	KASJK7FR01	R	060UFEMIK7EA0EE	R	HM		18850040	+	03000			A	JS

[illegible][illegible]

QUALITY
16
CHECKED

CITY AND STATE AHOSKIE, NC	ELEVATION: 67 AIRPORT NAME: TRI-COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 30 APRIL 2015	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ILTOJ	ILTOJ	010	IAF	HF	R	FO		008.5 (358.5T)	004.0	AA 03000	
		ILTOJ	010	FACF	IF		FB				AA 03000	
		EWIVO	020	FAF	TF		FB	0.5	008.5 (358.5T)	006.0	AA 01600	
		HALVA	021	SDF	TF		FB	0.3	008.5 (358.5T)	002.9	AA 00600	GS 00612
		RW01	030	MAP	TF		FO	0.3	008.5 (358.5T)	001.5	AT 00108	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		008.5 (358.5T)		AA 00322	
		UFEMI	050		DF		FO				AA 03000	
		UFEMI	060		HM	R	FO		188.5 (178.5T)	004.0	AA 03000	
POINT DATA		WAYPOINT			LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS	
		EWIVO			N361302.47		W0771005.43		N3613.041		W07710.091	
		HALVA			N361558.74		W0771011.32		N3615.979		W07710.189	
		ILTOJ			N360702.09		W0770953.42		N3607.035		W07709.890	
		UFEMI			N362856.11		W0771037.36		N3628.935		W07710.623	
		RW01			N361728.85		W0771014.33		N3617.481		W07710.239	
RUNWAY DATA		RWY		THRESHOLD ELEVATION		TCH						
		RW01		00067		41						



CITY AND STATE AHOSKIE, NC	ELEVATION: 67	TDZE: 67	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 1, ORIG 30 APRIL 2015	SUP:
	AIRPORT NAME:		RNAV		AMDT: NONE
	TRI-COUNTY				DATED: