


US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.	
TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: WISID CLIMBING RIGHT TURN TO 3500 DIRECT ZOSLO AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 479 AAO 333236N/0884419W CHART GOLDEN TRIANGLE AWOS-3. CHART CIRCLING ICON. CHART COLUMBUS MOA.	
ZOSLO (IF/IAF)	WULEN (FB)	139.69 / 5.97	1800		
WULEN (FAF)	WISID (MAP) (FO)	139.74 / 4.25	3500		
WISID (MAP)	650 MSL	139.74			
650 MSL	ZOSLO (FO)				
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD NW ZOSLO, RT, 139.69 INBOUND, 3500 FT. IN LIEU OF PT (IAF) 3. FAC: 139.74 FAF: WULEN DIST FAF TO MAP: 4.25 THLD: <u> </u> 4. MIN. ALT: ZOSLO 3500, WULEN 1800 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 2E EPOCH YEAR: 1990	
MINIMUMS					
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A ☐ X ☐		
CATEGORY =====>	A		B		C
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS
CIRCLING	760	1	510	840	1
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: USE GOLDEN TRIANGLE RGNL ALTIMETER SETTING; WHEN NOT RECEIVED, USE GEORGE M BRYAN ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET.					
CITY AND STATE STARKVILLE, MS		ELEVATION: 250 TDZE: AIRPORT NAME: OKTIBBEHA		FACILITY IDENTIFIER: RNAV PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 11 DECEMBER 2014	
				SUP: AMDT: NONE DATED	



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	050/30 CW 230/30 (NOPT)	ZOSLO (IF/IAF) (FB)	3500
2.	230/30 CW 050/30	ZOSLO (IF/IAF) (FO)	3500

QUALITY
6
CHECKED

CITY AND STATE
STARKVILLE, MS

ELEVATION: 250 TDZE:
AIRPORT NAME:
OKTIBBEHA

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-A, ORIG
11 DECEMBER 2014

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP M51 K7FRNV-A AZOSLO	010Z	ZOSLOK7EA0EE	AR	HF			13970040		+ 03500	18000			B JC
SUSAP M51 K7FRNV-A R	010Z	ZOSLOK7EA0E	I	IF					+ 03500	18000			B JC
SUSAP M51 K7FRNV-A R	020W	ULENK7EA0E	F	051TF			13970060		+ 01800				B JC
SUSAP M51 K7FRNV-A R	030W	SIDK7EA0EY	M	031TF			13970043			000			B JC
SUSAP M51 K7FRNV-A R	040		0	M	CA		1397		+ 00650				B JC
SUSAP M51 K7FRNV-A R	050Z	ZOSLOK7EA0EY	R	DF					+ 03500				B JC
SUSAP M51 K7FRNV-A R	060Z	ZOSLOK7EA0EE	R	HM			13970040		+ 03500				B JC

[illegible]

QUALITY
CHECKED

CITY AND STATE STARKVILLE, MS	ELEVATION: 250	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, ORIG 11 DECEMBER 2014	SUP:
	AIRPORT NAME: OKTIBBEHA				AMDT: NONE
					DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ZOSLO	ZOSLO	010	IAF	HF	R	FO		139.7 (141.7T)	004.0	AA 03500	
		ZOSLO	010	FACF	IF		FB				AA 03500	
		WULEN	020	FAF	TF		FB	0.5	139.7 (141.7T)	006.0	AA 01800	
		WISID	030	MAP	TF		FO	0.3	139.7 (141.7T)	004.3	AT 00840	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		139.7 (141.7T)		AA 00650	
	ZOSLO	050		DF	R	FO				AA 03500	
	ZOSLO	060		HM	R	FO		139.7 (141.7T)	004.0	AA 03500	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	WISID	N333025.53	W0884126.10	N3330.426	W08841.435
	WULEN	N333346.39	W0884435.17	N3333.773	W08844.586
	ZOSLO	N333827.85	W0884900.66	N3338.464	W08849.011
	RW14	N333001.92	W0884103.90	N3330.032	W08841.065

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW14	00246	50

5
CHECK

CITY AND STATE STARKVILLE, MS	ELEVATION: 250	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, ORIG 11 DECEMBER 2014	SUP:
	AIRPORT NAME: OKTIBBEHA				AMDT: NONE
					DATED: