

<b>U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION</b> <b>NDB STANDARD INSTRUMENT APPROACH PROCEDURE</b> <b>FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27</b>								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
<b>TERMINAL ROUTES</b>										<b>MISSED APPROACH</b>						
<b>FROM</b>		<b>TO</b>		<b>COURSE AND DISTANCE</b>				<b>ALTITUDE</b>		<b>MAP: PLX NDB</b>						
LISLE INT		PLX NDB		261.59 / 13:60				2600		<b>CLIMBING LEFT TURN TO 2200 IN PLX NDB HOLDING PATTERN.</b>  <b>ADDITIONAL FLIGHT DATA:</b> HOLD NW, LT, 156.39 INBOUND. FAS OBST: 799 AAO 390451N/0874118W CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 3002 FROM THLD.						
1. PT <u>R</u> SIDE OF COURSE <u>336.39</u> OUTBOUND <u>2200</u> FT WITHIN <u>10</u> MILES OF <u>PLX NDB</u> (IAF)														MAG VAR: 3W EPOCH YEAR: 2015		
2. _____																
3. FAC <u>156.39</u> FAF _____ DIST FAF TO MAP _____ THLD _____																
4. MIN. ALT _____																
8. MSA FROM: PLX NDB 2600																
<b>MINIMUMS</b>																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N/A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-17	1160	1	705	1160	1	705	1160	2	705	1160	2	705				
CIRCLING	1160	1	699	1160	1	699	1160	2	699	1180	2 1/4	719				
<b>NOTES:</b> CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRE HAUTE INTL - HULMAN FIELD ALTIMETER SETTING AND INCREASE ALL MDA 100 FT; INCREASE S-17 CAT B VISIBILITY 1/4 MILE AND CATS C/D VISIBILITY 1/2 MILE, INCREASE CIRCLING CAT B VISIBILITY 1/4 MILE AND CATS C/D VISIBILITY 1/2 MILE. (SEE FORM 8260-10)																
CITY AND STATE				ELEVATION: 461      THRE: 455		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP				
ROBINSON, IL				AIRPORT NAME:		PLX		NDB RWY 17, AMDT 8 19 SEPTEMBER 2013				AMDT      7A				
				CRAWFORD CO								DATE      04/07/2011				

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**NOTES, (CONT.):****CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.****CHART NOTE: RWY 17 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.**

QUALITY  
2  
CHECKED

CITY AND STATE  
ROBINSON, IL

ELEVATION: 461      THRE: 455  
AIRPORT NAME:  
CRAWFORD CO

FACILITY  
IDENTIFIER:  
PLX

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:  
NDB RWY 17, AMDT 8  
19 SEPTEMBER 2013

SUP:  
AMDT: 7A  
DATED: 04/07/2011