

PAGE 1 OF 6 PAGES

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
NACIT/2.80 NM TO RW09	RW09 (MAP) (FO)	094.74 / 2.80	
RW09 (MAP)	805 MSL	094.74	
805 MSL	JIXUT (FO)		2200

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON BIB VORTAC AIRWAY RADIALS 012 CW 078.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

*LNAV ONLY

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TERRE HAUTE INTL-HULMAN FIELD ALTIMETER

SETTING AND INCREASE ALL DA 89 FEET AND ALL MDA 100 FEET; INCREASE LPV ALL CATS VISIBILITY 1/4

MILE, INCREASE LNAV CATS C/D VISIBILITY 1/4 MILE, AND CIRCLING CATS C/D VISIBILITY 1/2 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: RWY 09 STRAIGHT-IN AND CIRCLING MINIMUMS NA AT NIGHT.

QUALITY
2
CHECKED

CITY AND STATE
ROBINSON, IL

ELEVATION: 461 THRE: 461
AIRPORT NAME:
CRAWFORD CO

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 9, AMDT 1
22 AUGUST 2013

SUP:
AMDT: ORIG
DATED: 09/25/2008

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Cellings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRSV
RUNWAY	RW09
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W09A
REFERENCE PATH IDENTIFIER (APPROACH ID)	390059.9085N
LTP/FTP LATITUDE	0873939.5725W
LTP/FTP LONGITUDE	+01087
LTP/FTP ELLIPSOIDAL HEIGHT	390057.0760N
FPAP LATITUDE	0873745.3115W
FPAP LONGITUDE	00040.0
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	1192
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	50.0
VERTICAL ALERT LIMIT (VAL)	

CRC REMAINDER

5CFA3521

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+01406
FPAP ORTHOMETRIC HEIGHT	+01406

QUALITY
2
CHECKED

CITY AND STATE ROBINSON, IL	ELEVATION: 461	THRE: 461	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 22 AUGUST 2013	SUP:	
	AIRPORT NAME:				AMDT:	ORIG
	CRAWFORD CO				DATED:	09/25/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KRSVK5FR09	ABIB	010BIB	K5D 0V	A	IF				18000		A	JS
SUSAP	KRSVK5FR09	ABIB	020PULOYK5EA0EE	B	010TF		08010277	+	02200			A	JS
SUSAP	KRSVK5FR09	ALUPCE	010LUPCEK5EA0E		IF					18000		A	JS
SUSAP	KRSVK5FR09	ALUPCE	0200ZIROK5EA0E	A	020TF		26400278	+	02600			A	JS
SUSAP	KRSVK5FR09	ALUPCE	030PULOYK5EA0EE	B	010TF		18470088	+	02200			A	JS
SUSAP	KRSVK5FR09	APULOY	010PULOYK5EA0EE	AR	HF		09470040	+	02200		18000	A	JS
SUSAP	KRSVK5FR09	ASAM	010SAM	K5D 0V	A	IF				18000		A	JS
SUSAP	KRSVK5FR09	ASAM	020PULOYK5EA0EE	B	010TF		01770333	+	02200			A	JS
SUSAP	KRSVK5FR09	R	010PULOYK5EA0E	I	IF			+	02200		18000	A	JS
SUSAP	KRSVK5FR09	R	020PEGEGK5EA1E	F	051TF		09470061	+	02200		RW09	K5PGA	JS
SUSAP	KRSVK5FR09	R	020PEGEGK5EA2WALPV			ALNAV/VNAV	ALNAV						JS
SUSAP	KRSVK5FR09	R	021NACITK5EA0E	S	031TF		09470025	V	0138001393		-300		A
SUSAP	KRSVK5FR09	R	030RW09	K5PGOGY	M	031TF	09470028		00501		-300		A
SUSAP	KRSVK5FR09	R	040		M	CA	0947	+	00805				A
SUSAP	KRSVK5FR09	R	050JIXUTK5EA0EY		DF			+	02200				A
SUSAP	KRSVK5FR09	R	060JIXUTK5EA0EE	R	HM		27500040	+	02200				A

[illegible]

CITY AND STATE ROBINSON, IL	ELEVATION: 461	THRE: 461	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS) RWY 9, AMDT 1	AMDT: ORIG
	CRAWFORD CO		RNAV	22 AUGUST 2013	DATED: 09/25/2008

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE ROBINSON, IL	ELEVATION: 461 THRE: 461 AIRPORT NAME: CRAWFORD CO	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 22 AUGUST 2013	SUP:
				AMDT: ORIG
				DATED: 09/25/2008

QUALITY
2
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
BIB		BIB	010	IAF	IF		FB					
BIB		PULOY	020		TF		FB	1.0	080.1 (077.1T)	027.7	AA 02200	
LUPCE		LUPCE	010		IF		FB					
LUPCE		OZIRO	020	IAF	TF		FB	2.0	264.0 (261.0T)	027.8	AA 02600	
LUPCE		PULOY	030		TF		FB	1.0	184.7 (181.7T)	008.8	AA 02200	
PULOY		PULOY	010	IAF	HF	R	FO		094.7 (091.7T)	004.0	AA 02200	
SAM		SAM	010	IAF	IF		FB					
SAM		PULOY	020		TF		FB	1.0	017.7 (014.7T)	033.3	AA 02200	
		PULOY	010	FACF	IF		FB				AA 02200	
		FELEG	020	FAF	TF		FB	0.5	094.7 (091.7T)	006.1	AA 02200	
		NACIT	021	SDF	TF		FB	0.3	094.7 (091.7T)	002.5	AA 01380	GS 01393
		RW09	030	MAP	TF		FO	0.3	094.7 (091.7T)	002.8	AT 00501	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		094.7 (091.7T)		AA 00805	
	JIXUT	050		DF		FO				AA 02200	
	JIXUT	060		HM	R	FO		275.0 (272.0T)	004.0	AA 02200	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BIB	N385513.24	W0882854.50	N3855.221	W08828.908
	SAM	N382906.68	W0880508.90	N3829.111	W08805.148
	FELEG	N390109.83	W0874630.02	N3901.164	W08746.500
	JIXUT	N390035.73	W0872400.88	N3900.596	W08724.015
	LUPCE	N391435.94	W0871837.50	N3914.599	W08718.625
	NACIT	N390105.17	W0874315.02	N3901.086	W08743.250
	OZIRO	N391008.89	W0875357.18	N3910.148	W08753.953
	PULOY	N390120.62	W0875416.81	N3901.344	W08754.280
	RW09	N390059.91	W0873939.57	N3900.999	W08739.660

RUNWAY DATA	THRESHOLD	TCH
RWY	ELEVATION	
RW09	00461	40

QUALITY
2
CHECKED

CITY AND STATE ROBINSON, IL	ELEVATION: 461	THRE: 461	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 9, AMDT 1 22 AUGUST 2013	SUP:
	AIRPORT NAME: CRAWFORD CO				AMDT: ORIG
					DATED: 09/25/2008