

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
LOUISBURG, NC	TRIANGLE NORTH EXECUTIVE	20 OCT 2011	ORIG

TAKEOFF MINIMUMS:

RWY 05, 23 STANDARD

TEXTUAL DEPARTURE PROCEDURES:

RWY 05 – CLIMB HEADING 046.48 TO 1900 BEFORE TURNING RIGHT

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 05, TREES BEGINNING 154 FT FROM DER, 516 FT RIGHT OF CENTERLINE, UP TO 99 FT AGL/ 399 FT MSL. TREES BEGINNING 166 FT FROM DER, 492 FT LEFT OF CENTERLINE, UP TO 75 FT AGL/ 415 FT MSL. TERRAIN 471 FT FROM DER, 394 FT LEFT OF CENTERLINE, 345 MSL.

NOTE: RWY 23, VEHICLE ON ROAD 98 FT FROM DER, 457 FT RIGHT OF CENTERLINE, UP TO 15 FT AGL/ 377 FT MSL. POWER LINE 760 FT FROM DER, 635 FT RIGHT OF CENTERLINE, 55 FT AGL/405 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 05 - 1549 FT MSL TOWER 360613.00N/0781127.00W.

QUALITY
CHECKED