

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ISMOJ (IAF)	OGKIP (NOPT) (FB)	273.81 / 5.00	2000	LNAV: RW36
EHGOP (IAF)	OGKIP (NOPT) (FB)	093.71 / 5.00	2000	CLIMB TO 2000 DIRECT OZMOP AND HOLD.
OGKIP (IF/IAF)	OLJAF (FB)	003.76 / 6.10	1600	
				ADDITIONAL FLIGHT DATA: HOLD N, RT, 183.76 INBOUND. CHART FAS OBST: 155 TREE 300317N/0833514W OLJAF TO RW36: 3.04/45.

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S OGKIP, RT, 003.76 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
- FAC: 003.76 FAF: OLJAF DIST FAF TO MAP: 4.69 THLD: 4.69
- MIN. ALT: OGKIP 2000, OLJAF 1600, TEPTE/2.20 NM TO RW36 780
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCP: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: 34:1 IS NOT CLEAR
- MSA FROM:

MAG VAR: 3W EPOCH YEAR: 2000

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	460	1	418	460	1	418	460	1 1/4	418	460	1 1/4	418			
CIRCLING	620	1	576	620	1	576	620	1 1/2	576	860	2 3/4	816			

NOTES:
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 CHART PROFILE NOTE: VGS AND DESCENT ANGLES NOT COINCIDENT.
 CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TALLAHASSEE ALTIMETER SETTING AND SEE 8260-10

@ CAT D 900-2 3/4
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.



CITY AND STATE PERRY, FL	ELEVATION: 44 TDZE: 42 AIRPORT NAME: PERRY-FOLEY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 23 SEP 2010	SUP: AMDT: ORIG-B DATED 06/04/2009
-----------------------------	--------------------------------------------------------	------------------------------	------------------------------------------------------------------------------------	------------------------------------------

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.
INCREASE ALL MDA 120 FEET; INCREASE LNAV CAT C AND CIRCLING CAT D VISIBILITY 1/4 MILE, AND CIRCLING CAT C VISIBILITY 1/2 MILE.

TAA	FROM	TO	ALT
1.	274/30 CW 094/30 (NOPT)	OGKIP (IF/IAF)	2000
2.	094/30 CW 184/30	EHGOP (IAF)	2000
3.	184/30 CW 274/30	ISMOJ (IAF)	2000



CITY AND STATE PERRY, FL	ELEVATION: 44 TDZE: 42 AIRPORT NAME: PERRY-FOLEY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, AMDT 1 23 SEP 2010	SUP:
				AMDT: ORIG-B
				DATED: 06/04/2009

