

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 13, 26 STANDARD.

RWY 8, 300-1 1/4 OR STANDARD WITH MINIMUM CLIMB OF 301 FT PER NM TO 700.

RWY 31, 300-1 1/2 OR STANDARD WITH MINIMUM CLIMB OF 210 FT PER NM TO 700, OR ALTERNATIVELY WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1300 FT PRIOR TO DEPARTURE END OF RUNWAY.

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 8 - CLIMB HEADING 076.96 TO 800 BEFORE TURNING LEFT.

(3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 8, SILO 590' FROM DER, 637' RIGHT OF CENTERLINE, 88' AGL/427' MSL. TREES BEGINNING 825' FROM DER, 41' RIGHT OF CENTERLINE, UP TO 100' AGL/425' MSL. TREES BEGINNING 1336' FROM DER, 281' LEFT OF CENTERLINE, UP TO 100' AGL/579' MSL.

NOTE: RWY 13, TREES BEGINNING 2322' FROM DER, 902' RIGHT OF CENTERLINE, UP TO 100' AGL/499' MSL. TREES BEGINNING 615' FROM DER, 328' LEFT OF CENTERLINE, UP TO 43' AGL/442' MSL.

NOTE: RWY 26, VEHICLES ON ROAD BEGINNING 269' FROM DER, 494' RIGHT OF CENTERLINE, UP TO 15' AGL/403' MSL. TREE 1257' FROM DER, 797' RIGHT OF CENTERLINE, 59' AGL/439' MSL.

(4) CONTROLLING OBSTACLES:

RWY 8: 710 MSL ELEVATORS 400859.00N-0761506.00W, 579 MSL TREE 400813.65N-0761557.57W, 539 MSL TREE 400815.34N-0761543.77W.

RWY 31: 571 TREE 400812.90N-0761915.65W, 571 MSL TREE 400813.25N-0761919.70W.



(5) City, State LANCASTER, PA	(6) Airport LANCASTER	(7) Effective Date 17 DEC 2009	(8) Amdt. No. 1
-----------------------------------------	---------------------------------	------------------------------------------	---------------------------

**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
DEPARTURE PROCEDURE (CONTINUATION FAA FORM 8260-15A)
FLIGHT STANDARDS SERVICE**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL.. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

(3) TAKEOFF OBSTACLE NOTES:

RWY 26 (CONT), TREES BEGINNING 1927' FROM DER, 915' LEFT OF CENTERLINE, UP TO 100' AGL/489' MSL.

NOTE: RWY 31, TREES BEGINNING 1334 FROM DER, 350' RIGHT OF CENTERLINE, UP TO 100' AGL/571' MSL. POLE 402' FROM DER, 221' LEFT OF CENTERLINE, 24' AGL/404' MSL. BUILDING 527' FROM DER, 229' LEFT OF CENTERLINE, 29' AGL/409' MSL. TREES BEGINNING 956' FROM DER, 88' LEFT OF CENTERLINE, UP TO 100' AGL/489' MSL.

QUALITY
9
CHECKED

City, State LANCASTER, PA		Airport LANCASTER			Effective Date 17 DEC 2009	Amdt. No. 1
DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date	