

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
BUMPASS, VA	LAKE ANNA	15 DEC 2011	ORIG

TAKEOFF MINIMUMS:

RWY 8, 26 STANDARD.

TEXTUAL DEPARTURE PROCEDURES:

RWY 8: CLIMB HEADING 084.64 TO 800 BEFORE TURNING.

RWY 26: CLIMB HEADING 264.64 TO 800 BEFORE TURNING.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 8, TREES BEGINNING 32 FEET FROM DER, 114 FEET RIGHT OF CENTERLINE, UP TO 100 FEET AGL, 469 FEET MSL.
BUILDINGS BEGINNING 162 FEET FROM DER, 152 FEET LEFT OF CENTERLINE, UP TO 25 FEET AGL, 384 FEET MSL.

NOTE: RWY 26, TREES BEGINNING 31 FEET FROM DER, 97 FEET LEFT AND 119 FEET RIGHT OF CENTERLINE, UP TO 100 FEET AGL,
459 FEET MSL.

CONTROLLING OBSTACLES:

RWY 8: 469 MSL TREE 375752.59N/0774500.70W

Rwy 26: 459 MSL TREE 375757.98N/0774428.62W.

