

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
QUAKERTOWN, PA	QUAKERTOWN	28 JUNE 2012	1

TAKEOFF MINIMUMS:

RWY 11, STANDARD
RWY 29, 300-1 OR STANDARD WITH MINIMUM CLIMB OF 730 FEET PER NM TO 800.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 11, MULTIPLE TREES, STRUCTURES AND POLES BEGINNING 19 FEET FROM DER, 1300 FEET LEFT OF CENTERLINE TO 1385 FEET RIGHT OF CENTERLINE, UP TO 100 FEET AGL/639 FEET MSL.
NOTE: RWY 29, MULTIPLE TREES, STRUCTURES AND POLES BEGINNING 27 FEET FROM DER, 1329 FEET LEFT OF CENTERLINE TO 1049 FEET RIGHT OF CENTERLINE, UP TO 100 FEET AGL/691 FEET MSL.

CONTROLLING OBSTACLES:

RWY 29: 691 FT MSL TREE 402602.31N/0752340.04W

