

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CAUDE	ILOZA (FB)	008.83 / 9.63	5400	LNAV: CIPLI CLIMBING LEFT TURN TO 5400 DIRECT CAUDE AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 298.27 INBOUND. FAS OBST: 3749 AAO 351612N/1013903W CHART P-47. CHART VDP AT 0.58 MILES TO CIPLI. ELTIC TO RW22: 3.00/50. CHART TRADEWIND (KTDW) AIRPORT. FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD. CHART ASR.
ILOZA (IAF)	ZUKTA (NOPT) (FB)	323.14 / 5.00	5400	
JUNVE (IAF)	ZUKTA (NOPT) (FB)	141.28 / 9.04	5400	
ZUKTA (IF/IAF)	ELTIC (FB)	233.11 / 7.00	5400	

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)

2. HOLD NE ZUKTA, LT, 233.11 INBOUND, 5400 FT. IN LIEU OF PT (IAF)

3. FAC: 233.04 FAF: ELTIC DIST FAF TO MAP: 5.00 THLD: 5.48

4. MIN. ALT: ZUKTA 5400, ELTIC 5400

5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:

6. MIN GS INCPT: GS ALT AT: OM: MM: IM:

7. GS ANGLE: TCH: 34:1 IS CLEAR

8. MSA FROM: CIPLI 6100

MAG VAR: 8E EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A		STANDARD @								
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	4020	1/2	414	4020	1/2	414	4020	3/4	414	4020	1	414	4020	1	414
CIRCLING	4080	1	473	4080	1	473	4080	1 1/2	473	4240	2	633	4460	3	853

NOTES:
 CHART NOTE: FOR INOPERATIVE MALSR, INCREASE LNAV CAT D VISIBILITY TO 1 1/4 MILE AND CAT E VISIBILITY TO 1 1/2 MILE.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART PROFILE NOTE: VGS1 AND DESCENT ANGLES NOT COINCIDENT.
 SEE 8260-10

@ CAT E 900-3
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

QUALITY
 &
 CHECKED

CITY AND STATE AMARILLO, TX	ELEVATION: 3607 TDZE: 3606 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 22, AMDT 1 13 JAN 2011	SUP: RNAV (GPS) RWY 22 AMDT: ORIG-A DATED 07/06/2006
---------------------------------------	--	-------------------------------------	--	---

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BORGER ALTIMETER SETTING AND INCREASE

ALL MDA 160 FEET, INCREASE LNAV CAT C VISIBILITY 1/4 MILE, CAT D VISIBILITY 3/4 MILE, CAT E VISIBILITY 1 MILE, CIRCLING CAT C VISIBILITY 1/4 MILE AND CAT D VISIBILITY 1/2 MILE.

CHART NOTE: VDP NA WITH BORGER ALTIMETER SETTING.

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV CATS D AND E WITH BORGER ALTIMETER SETTING.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JUNVE ON V304 NORTHBOUND.

QUALITY
CHECKED

CITY AND STATE

AMARILLO, TX

ELEVATION: 3607 TDZE: 3606

AIRPORT NAME:

RICK HUSBAND AMARILLO INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) Y RWY 22, AMDT 1

13 JAN 2011

SUP: RNAV (GPS) RWY 22

AMDT: ORIG-A

DATED: 07/06/2006

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KAMAK4FR22-Y	ACAUDE	010CAUDEK4EA0E	IF						18000		B JS	
SUSAP	KAMAK4FR22-Y	ACAUDE	020ILOZAK4EA0E	A 020TF		00860096		+ 05400				B JS	
SUSAP	KAMAK4FR22-Y	ACAUDE	030ZUKTAK4EA0EE	B 010TF		32310050		+ 05400				B JS	
SUSAP	KAMAK4FR22-Y	AJUNVE	010JUNVEK4EA0E	A IF						18000		B JS	
SUSAP	KAMAK4FR22-Y	AJUNVE	020ZUKTAK4EA0EE	B 010TF		14130090		+ 05400				B JS	
SUSAP	KAMAK4FR22-Y	AZUKTA	010ZUKTAK4EA0EE	AL HF		23310050		+ 05400		18000		B JS	
SUSAP	KAMAK4FR22-Y	R	010ZUKTAK4EA0E	I IF				+ 05400		18000		B JS	
SUSAP	KAMAK4FR22-Y	R	020ELTICK4EA1E	F 051TF		23310070		+ 05400			CIPLI K4EAB	JS	
SUSAP	KAMAK4FR22-Y	R	020ELTICK4EA2WN		N	ALNAV						JS	
SUSAP	KAMAK4FR22-Y	R	030CIPLIK4EA0EY	M 031TF		23300050		03809		-300		B JS	
SUSAP	KAMAK4FR22-Y	R	040	0 M 010CA		2330		+ 04007				B JS	
SUSAP	KAMAK4FR22-Y	R	050CAUDEK4EA0EY	L010DF				+ 05400				B JS	
SUSAP	KAMAK4FR22-Y	R	060CAUDEK4EA0EE	R020HM		29830050		+ 05400				B JS	

QUALITY
4
CHECKED

PAGE 3 OF 4 PAGES

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE AMARILLO, TX	ELEVATION: 3607 TDZE: 3606 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 22, AMDT 1 13 JAN 2011	SUP. RNAV (GPS) RWY 22
				AMDT: ORIG-A
				DATED: 07/06/2006

PAGE 4 OF 4 PAGES