

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
HERINGTON, KS	HERINGTON RGNL	13 JAN 2011	ORIG

TAKEOFF MINIMUMS:

RWY 35: STANDARD.

RWY 17: 400 - 2 1/2 OR STANDARD WITH MINIMUM CLIMB OF 215 FT PER NM TO 2000, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT PER NM CLIMB GRADIENT. TAKEOFF MUST OCCUR NO LATER THAN 1800 FT PRIOR TO DER.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE RWY 17: TOWER 2.0 NM FROM DER, 3564 FT RIGHT OF CENTERLINE, 318 FT AGL/1808 FT MSL.

CONTROLLING OBSTACLES:

RWY 17: 1808 MSL TOWER 383917.00N/0964914.00W.

