

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
OSCEOLA, IA	OSCEOLA MUNI	15 DEC 2011	ORIG

TAKEOFF MINIMUMS:

RWY 18, 36, STANDARD

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

RWY 18, NAVAID AND ROAD BEGINNING 40 FT FROM DER, 49 FT LEFT OF CENTERLINE, UP TO 12 FT AGL/1131 FT MSL. NAVAID, TREES, AND ROAD BEGINNING 12 FT FROM DER, 3 FT RIGHT OF CENTERLINE, UP TO 13 FT AGL/1132 FT MSL.

RWY 36, TREES BEGINNING 794 FT FROM DER, 225 FT LEFT OF CENTERLINE, UP TO 57 FT AGL/1166 FT MSL. TREES AND POLE BEGINNING 581 FT FROM DER, 415 FT RIGHT OF CENTERLINE, UP TO 48 FT AGL/1157 FT MSL.

CONTROLLING OBSTACLES:

QUICK
CHECKED