

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
STILLWATER, OK	STILLWATER RGNL	20 OCT 2011	ORIG

TAKEOFF MINIMUMS:

RWY 4, 17, 22, 35: STANDARD

TEXTUAL DEPARTURE PROCEDURES:

RWY 17- CLIMB HEADING 174.49 TO 1600 BEFORE TURNING RIGHT.

RWY 22- CLIMB HEADING 219.50 TO 2500 BEFORE TURNING RIGHT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 4: FENCE 191 FT FROM DER, 271 FT LEFT OF CENTERLINE, 11 FT AGL/991 FT MSL. TREE 857 FT FROM DER, 545 FT LEFT OF CENTERLINE, 30 FT AGL/1020 FT MSL. TREE 498 FT FROM DER, 331 FT RIGHT OF CENTERLINE, 26 FT AGL/1006 FT MSL.

NOTE: RWY 17: BUILDING AND TREES BEGINNING 1075 FT FROM DER, FROM 540 FT LEFT OF CENTERLINE, UP TO 60 FT AGL/1019 FT MSL.

NOTE: RWY 22: TREES BEGINNING 1158 FT FROM DER, 770 FT LEFT OF CENTERLINE, UP TO 60 FT AGL/1029 FT MSL.

NOTE: RWY 35: TREES BEGINNING 94 FT FROM DER, 229 FT LEFT OF CENTERLINE, UP TO 60 FT AGL/1059 FT MSL. TREES BEGINNING 782 FT FROM DER, 669 FT RIGHT OF CENTERLINE, UP TO 60 FT AGL/1039 FT MSL. PLANT 1688 FT FROM DER, 729 FT RIGHT OF CENTERLINE, 79 FT AGL/1059 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 17, 22- 2063 FT MSL TOWER, 360630.40N/0971147.10W.

