

U.S. DEPARTMENT OF TRANSPORTATION -- FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
CROCKETT, TX	HOUSTON COUNTY	15 DEC 2011	ORIG

TAKEOFF MINIMUMS:

RWY 2: 400-2 OR STANDARD WITH A MINIMUM CLIMB OF 280 FT PER NM TO 800.

RWY 20: 300-1 ½ OR STANDARD WITH A MINIMUM CLIMB OF 459 FT PER NM TO 700.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 2, MULTIPLE TREES BEGINNING 57 FT FROM DER, 61 FT RIGHT OF CENTERLINE, UP TO 50 FT AGL/399 FT MSL. MULTIPLE TREES AND TERRAIN BEGINNING 27 FT FROM DER, 109 FT LEFT OF CENTERLINE, UP TO 50 FT AGL/409 FT MSL. TOWER 1.5 NM FROM DER, 2864 FT LEFT OF CENTERLINE 233 FT AGL/623 FT MSL.

NOTE: RWY 20, MULTIPLE TOWERS BEGINNING 4567 FT FROM DER, 1025 FT RIGHT OF CENTERLINE, UP TO 200 FT AGL/529 FT MSL.

CONTROLLING OBSTACLES:

RWY 2: 623 FT MSL TOWER 312019.00N/0952357.00W.

RWY 20: 519 FT MSL TOWER 311701.36N/0952505.11W, 529 FT MSL TOWER 311729.57N/0952456.27W.

ORIGINAL
4
CHECKED