

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
HAMILTON, AL	MARION COUNTY-RANKIN FITE	15 DEC 2011	1

**TAKEOFF MINIMUMS:**

RWY 18: 400 – 2 ½ OR STANDARD WITH MINIMUM CLIMB OF 390 FT PER NM TO 800.  
RWY 36: 400 – 2 ¼ OR STANDARD WITH MINIMUM CLIMB OF 370 FT PER NM TO 900.

**TEXTUAL DEPARTURE PROCEDURES:**

RWY 18: CLIMB HEADING 180.88 TO 900 BEFORE TURNING LEFT.  
RWY 36: CLIMB HEADING 000.88 TO 1000 BEFORE TURNING LEFT.

**TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 18, TREES BEGINNING 53 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/699 FT MSL. TREES BEGINNING 1.5 NM FROM DER, 2172 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/719 FT MSL.

NOTE: RWY 36, TREES BEGINNING 122 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/573 FT MSL. BUILDING 2368 FT FROM DER, 411 FT RIGHT OF CENTERLINE, 50 FT AGL/501 FT MSL. VEHICLES ON ROADWAY BEGINNING 2511 FT FROM DER, 1124 FT LEFT OF CENTERLINE, UP TO 17 FT AGL/516 FT MSL. POLE 3009 FT FROM DER, 309 FT LEFT OF CENTERLINE, 70 FT AGL/569 FT MSL. TOWERS AND TREES BEGINNING 1.1 NM FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 115 FT AGL/779 FT MSL.

**CONTROLLING OBSTACLES:**

RWY 18: 699 FT MSL TREE, 340534.71N/0875933.34W; 719 FT MSL TREE, 340433.75N/0875923.06W.  
RWY 36: 739 FT MSL TREE, 340833.44N/0880002.16W; 739 FT MSL TREE, 340924.48N/0880029.06W; 779 FT MSL TREE, 340920.20N/0880029.45W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 18 – 860 FT MSL TOWER, 340451.00N/0875832.00W.  
RWY 36 – 879 FT MSL TOWER, 340920.60N/0880042.80W.

**REMARKS:**

