## U.S. DEPARTMENT of TRANSPORTATION

#### FEDERAL AVIATION ADMINISTRATION

# TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

#### (1) TAKEOFF MINIMUMS: RWY 11. 29 STANDARD

(2) DEPARTURE PROCEDURE:

### (3) TAKEOFF OBSTACLE NOTES:

NOTE: RWY 29, ROD ON AIRPORT BEACON OBSTRUCTION LIGHT, 138 FEET FROM DER, 514 FEET RIGHT OF CENTERLINE, 61 FEET AGL/67 FEET MSL; POLE, 82 FEET FROM DER, 403 FEET LEFT OF CENTERLINE, 34 FEET AGL/40 FEET MSL; POLE, 468 FEET FROM DER, 508 FEET RIGHT OF CENTERLINE, 37 FEET AGL/43 FEET MSL; HANGER, 221 FEET FROM DER, 278 FEET RIGHT OF CENTERLINE, 22 FEET AGL/28 FEET MSL; POLE, 490 FEET FROM DER, 306 FEET LEFT OF CENTERLINE, 28 FEET AGL/34 FEET MSL; TREE, 987 FEET FROM DER, 476 FEET LEFT OF CENTERLINE, 40 FEET AGL/46 FEET MSL; TREE 1287 FEET FROM DER, 432 FEET LEFT OF CENTERLINE, 47 FEET AGL/53 FEET MSL; TREE 1415 FEET FROM DER, 560 FEET LEFT OF CENTERLINE, 48 FEET AGL/54 FEET MSL; (CONTINUED ON PAGE 2)

### (4) CONTROLLING OBSTACLES:

RWY 29: 67 MSL ROD ON AIRPORT BEACON OBSTRUCTION LIGHT, 082040.91/804126.31; 40 MSL POLE 282032.16/804129.12; 43 MSL POLE, 282041.94/804129.82; 28 MSL HANGER, 282038.98/804128.06; 34 MSL POLE, 282034.41/804133.07; 46 MSL TREE, 282034.45/804138.95; 53 MSL TREE, 282035.84/804141.95; 54 MSL TREE 282035.07/804143.78; 31 MSL BLDG, 282042.44/804130.67; 54 MSL TREE, 282045.42/804142.50; 25 MSL OBSTRUCTION LIGHT ON WINDSOCK, 282039.65/804131.71; 43 MSL POLE, 282042.36/804139.59; 21 MSL BLDG, 282041.14/804129.67; 55 MSL TREE, 282037.17/804149.32

(5) City, State	(6) Airport	(7) Effective Date		(8) Amdt. No.
MERRITT ISLAND, FL	MERRITT ISLAND	APA 13	2006	ORIG
				_

FAA Form 8260-15A / February 2003 (computer generated)

Page 1 of 2 Pages

## U.S. DEPARTMENT of TRANSPORTATION

#### FEDERAL AVIATION ADMINISTRATION

## TAKEOFF MINIMUMS AND TEXTUAL DEPARTURE PROCEDURES (DP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

### (1) TAKEOFF MINIMUMS:

(2) DEPARTURE PROCEDURE:

(3) TAKEOFF OBSTACLE NOTES: (CONTINUED FROM PAGE 1) BUILDING, 556 FEET FROM DER, 530 FEET RIGHT OF CENTERLINE, 25 FEET AGL/31 FEET MSL; TREE, 1654 FEET FROM DER, 464 FEET RIGHT OF CENTERLINE, 48 FEET AGL/54 FEET MSL; OBSTRUCTION LIGHT ON WINDSOCK, 551 FEET FROM DER, 234 FEET RIGHT OF CENTERLINE, 19 FEET AGL/25 FEET MSL; POLE, 1306 FEET FROM DER, 259 FEET RIGHT OF CENTERLINE, 37 FEET AGL/43 FEET MSL; BUILDING, 429 FEET FROM DER, 436 FEET RIGHT OF CENTERLINE, 15 FEET AGL/21 FEET MSL; TREE, 1953 FEET FROM DER, 524 FEET LEFT OF CENTERLINE, 49 FEET AGL/55 FEET MSL.

(4) CONTROLLING OBSTACLES:

(5) City, State	(6) Airport	(7) Effective Date	(8) Arndt. No.
MERRITT ISLAND, FL	MERRITT ISLAND	3 2006	ORIG

FAA Form 8260-15A / February 2003 (computer generated)

Page 2 of 2 Pages