

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
TAMPA, FL	TAMPA EXECUTIVE	01/13/2011	1

TAKEOFF MINIMUMS:

RWY 5, 23, 36 STANDARD.

RWY 18, STANDARD WITH MINIMUM CLIMB OF 230 FT PER NM TO 900, OR 900 – 2 ½ FOR CLIMB IN VISUAL CONDITIONS.

TEXTUAL DEPARTURE PROCEDURES:

RWY 5, CLIMB HEADING 046.41 TO 500 BEFORE TURNING LEFT.

RWY 18, FOR CLIMB IN VISUAL CONDITIONS CROSS TAMPA EXECUTIVE AIRPORT AT OR ABOVE 800 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 5, TREES BEGINNING 1920 FT FROM DER, 45 FT RIGHT OF CENTERLINE, UP TO 70 FT AGL/95 FT MSL. TRESS BEGINNING 925 FT FROM DER, 343 FT LEFT OF CENTERLINE, UP TO 64 FT AGL/149 FT MSL.

NOTE: RWY 18, THREE LIGHT POLES BEGINNING 2894 FT FROM DER, 12 FT RIGHT OF CENTERLINE, UP TO 149 FT AGL/149 FT MSL. TREES BEGINNING 193 FT FROM DER, 287 FT LEFT OF CENTERLINE, UP TO 68 FT AGL/91 FT MSL. THREE LIGHT POLDES BEGINNING 2894 FT FROM DER, 5 FT RIGHT OF CENTERLINE, UP TO 129 FT AGL/149 FT MSL. LIGHT ON HANGER 287 FT FROM DER, 336 FT LEFT OF CENTERLINE, 24 FT AGL/44 FT MSL.

NOTE: RWY 23, TREES BEGINNING AT DER, 421 FT RIGHT OF CENTERLINE, UP TO 58 FT AGL/73 FT MSL. OL ON NAVAID 611 FT FROM DER, 258 FT LEFT OF CENTERLINE, 23 FT AGL/37 FT MSL. WINDSOCK 731 FT FROM DER, 258 FT RIGHT OF CENTERLINE, 24 FT AGL/38 FT MSL.

NOTE: RWY 36, TREES BEGINNING 37 FT FROM DER, 329 FT RIGHT OF CENTERLINE, UP TO 72 FT AGL/82 FT MSL. LIGHTED TOWER 3260 FT FROM DER, 348 FT RIGHT OF CENTERLINE, 105 FT AGL/122 FT MSL. TREES BEGINNING 1273 FT FROM DER, 158 FT LEFT OF CENTERLINE, UP TO 76 FT AGL/86 FT MSL. ANTENNA 627 FT FROM DER, 629 FT LEFT OF CENTERLINE, 78 FT AGL/88 FT MSL.

CONTROLLING OBSTACLES:

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 5 – 476 FT MSL TOWER 280347.00N/0821948.00W.

RWY 18 - 632 FT MSL TOWER 275641.42N/0822150.72W,

RWY 18 (VCOA) – 476 FT MSL TOWER 280347.00N/0821948.00W.

ALTA
6
CHECKED