

ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.														
TERMINAL ROUTES											MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA CLIMB TO 3100 DIRECT LURKY AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 058.35 INBOUND. CHART: ASR. CHART PLANVIEW NOTE: RNAV 1-GPS OR RADAR REQUIRED.										
TOPSY (IF/IAF)		SUMLY (RNP 0.50)		238.36 / 7.02 (I-GMX)				1800												
SUMLY (FAF)		RW24 (MAP)		238.36 / 5.42																
RW24 (MAP)		226 MSL (CA)		238.36				3100												
226 MSL		LURKY (FO) (DF) (RNP 1.00)																		
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NE TOPSY, RT, 238.36 INBOUND, 2000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>238.36</u> FAF: <u>SUMLY</u> DIST FAF TO MAP: _____ THLD: _____ 4. MIN. ALT: TOPSY 2000, SUMLY 1800 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: 900 6. MIN GS INCPT: <u>1800</u> GS ALT AT: <u>SUMLY 1800</u> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>52.2</u> 8. MSA FROM: _____																	MAG VAR: 10W		EPOCH YEAR: 2020	
MINIMUMS																				
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD										
CATEGORY =====>		A		B		C		D		E										
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA					
S-ILS 24**	226	2400	200	226	2400	200	226	2400	200	226	2400	200								
NOTES: CHART NOTE: **RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA. CHART NOTE: RNAV 1-GPS REQUIRED. CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).																				
CITY AND STATE WILMINGTON, NC		ELEVATION: 32 TDZE: 26 AIRPORT NAME: WILMINGTON INTL		FACILITY IDENTIFIER: I-GMX		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS Z RWY 24, AMDT 1 17 AUGUST 2017						SUP:								
												AMDT: ORIG-B								
												DATED 09/17/2015								



**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	148/30 CW 328/30 (NOPT)	148/9 CW 328/9	2100
2.	148/9 CW 328/9	TOPSY (IF/IAF) (FB)	2000
3.	328/30 CW 148/30	TOPSY (IF/IAF) (FO)	3100

QUALITY
18
CHECKED

CITY AND STATE

WILMINGTON, NC

ELEVATION: 32

TDZE: 26

AIRPORT NAME:

WILMINGTON INTL

FACILITY
IDENTIFIER:

I-GMX

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

ILS Z RWY 24, AMDT 1

17 AUGUST 2017

SUP:

AMDT: ORIG-B

DATED: 09/17/2015