

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
21-Aug-14	NY	Elmira/Corning	Elmira/Corning Rgnl	4/9304	06/19/14	ILS OR LOC RWY 6, Amdt 5

FDC **4/9304** ELM IAP ELMIRA/CORNING RGNL, ELMIRA/CORNING, NY. ILS OR LOC RWY 6, AMDT 5... S-ILS 6 DA 1144. S-LOC 6 HAT 1376 ALL CATS. VIS CAT A 1 1/4. CONAC FIX MINIMUMS** S-LOC 6 HAT 1076 ALL CATS. CHANGE CIRCLING TO RWY 10 AND 28 NA AT NIGHT
 NOTE TO READ: NIGHT LANDING: RWY 10 NA. CHART TDZE 944
 DELETE THRE 940. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE PENN YAN ALTIMETER SETTING AND INCREASE ALL DA 73 FEET AND ALL MDA 80, AND INCREASE S-LOC 6 CAT B AND CONAC FIX MINIMUMS S-LOC 6 CATS C/D VISIBILITY 1/2 MILE; INOPERATIVE TABLE DOES NOT APPLY TO S-LOC 6 ALL CATS AND CONAC FIX MINIMUMS S-LOC 6 CATS C/D; FOR INOPERATIVE MALSR INCREASE S-ILS 6 ALL CATS VISIBILITY TO 7/8 MILE. THIS IS ILS OR LOC RWY 6, AMDT 5A. 1406171642-PERM