

**DEPARTMENT OF TRANSPORTATION**  
**FEDERAL AVIATION ADMINISTRATION - FLIGHT STANDARDS SERVICE**  
**DEPARTURE PROCEDURES/TAKEOFF MINIMUMS**

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH →  AAT  ATA  ALPA  AOPA  NBAA  APA  OTHER (Specify) MEM ARTCC

Takeoff Minimums:

Rwy 17, 300-1 or standard with minimum climb of 350' per NM to 500.  
 Rwy 35, 400-1 or standard with minimum climb of 370' per NM to 500.

Takeoff Obstructions:

Rwy 17: 267 Trees 332723/882243  
 Rwy 35: 257 Trees 332824/882243  
 506 Tower 332930/882414

IFR Departure Procedure:

Rwys 17, 35, climb runway heading to 600 before turning.

*clg by A.22 on 5/12/87/L.O.*

**DEVELOPED BY**

SIGNATURE *E. H. Kirkendall*  
 E. H. KIRKENDALL/W. C. EVANS

DATE 1/27/87

FIFO ATL

**APPROVED BY**

SIGNATURE *Robert J. Marlott*  
 ROBERT J. MARLOTT, Manager, ATL FIFO

DATE 1/27/87

CITY AND STATE

Columbus, MS

AIRPORT

Columbus-Lowndes County

EFFECTIVE DATE

Routine

AMDT. NO.

Original

