

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33			Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE			ALTITUDE		LNAV: RW16							
ISOPE (IF/IAF)		FINOS (FB)		164.96 / 5.00			2000		CLIMB TO 2000 DIRECT RISNE AND HOLD.							
FINOS (FAF)		RW16 (MAP) (FO)		164.97 / 5.19												
RW16 (MAP)		720 MSL		164.97												
720 MSL		RISNE (FO)					2000		ADDITIONAL FLIGHT DATA: HOLD S, RT, 345.02 INBOUND. CHART FAS OBST: 665 TOWER 304855N/0893024W FINOS TO RW16: 3.00/46.1. CHART CIRCLING ICON. CHART BOGALUSA AWOS-3PT.							
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD N ISOPE, RT, 164.96 INBOUND, 2100 FT. IN LIEU OF PT (IAF)																
3. FAC: 164.97 FAF: FINOS DIST FAF TO MAP: 5.19 THLD: 5.19																
4. MIN. ALT: ISOPE 2100, FINOS 2000																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: _____ 34:1 IS NOT CLEAR																
8. MSA FROM: _____										MAG VAR: 2W EPOCH YEAR: 2020						
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X						
CATEGORY =====>		A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
CIRCLING	1040	1	720	1120	1	800	1120	2 1/4	800	1120	2 1/2	800				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE BOGALUSA ALTIMETER SETTING; WHEN NOT RECEIVED, USE HATTIESBURG ALTIMETER SETTING AND INCREASE ALL MDA 40 FEET AND INCREASE CIRCLING CAT B/C/D VISIBILITY 1/4 MILE. CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: PROCEDURE NA AT NIGHT.																
CITY AND STATE POPLARVILLE, MS		ELEVATION: 320 TDZE: AIRPORT NAME: POPLARVILLE-PEARL RIVER COUNTY			FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 10 DECEMBER 2015					SUP: AMDT: NONE DATED				

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	075/30 CW 255/30 (NOPT)	ISOPE (IF/IAF) (FB)	2100
2.	255/30 CW 075/30	255/15 CW 075/15	2800
	255/15 CW 075/15	ISOPE (IF/IAF) (FO)	2100

QUALITY
25
CHECKED

CITY AND STATE
POPLARVILLE, MS

ELEVATION: 320 TDZE:
AIRPORT NAME:
POPLARVILLE-PEARL RIVER COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-A, ORIG
10 DECEMBER 2015

SUP:
AMDT: NONE
DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - M13

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
ISOPE	010	ISOPE	HF	FO		165.0			R			AA 02100		EE A
	010	ISOPE	IF	FB								AA 02100		E I
	020	FINOS	TF	FB	0.5	165.0						AA 02000		E F
	030	RW16	TF	FO	0.3	165.0		3.00				AT 00349		GY M
	040		CA	FB		165.0						AA 00720		M
	050	RISNE	DF	FO								AA 02000		EY
	060	RISNE	HM	FO		345.0		R				AA 02000		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
FINOS	N305228.78	W0893208.80
ISOPE	N305716.27	W0893350.95
RISNE	N303708.34	W0892642.93

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW16	N304730.60	W0893023.04	00303	

QUALITY
25
CHECKED

CITY AND STATE POPLARVILLE, MS	ELEVATION: 320	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, ORIG 10 DECEMBER 2015	SUP:
	AIRPORT NAME: POPLARVILLE-PEARL RIVER COUNTY				AMDT: NONE
					DATED: