

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		ILS - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.29		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		ILS: DA LOC: 3.59 NM AFTER FLUFY LOM					
LFK VORTAC		FLUFY LOM		296.32 / 6.51				2000		CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 2000 DIRECT LFK VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD. ALTERNATE MA (DO NOT CHART): CLIMB TO 800 THEN CLIMBING RIGHT TURN TO 2400 DIRECT FLUFY LOM AND HOLD, CONTINUE CLIMB-IN-HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 331.56 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD W FLUFY LOM, RT, 073.24 INBOUND. FAS OBST: 419 AAO 311309N/0944914W CHART CIRCLING ICON. CHART IN PLANVIEW: (CFGBG) (311135.75N/0945615.75W).					
1. PT <u>R</u> SIDE OF COURSE <u>253.24</u> OUTBOUND <u>2000</u> FT WITHIN <u>10</u> MILES OF <u>FLUFY LOM</u> (IAF)										MAG VAR: 2E EPOCH YEAR: 2020					
2. _____															
3. FAC: <u>073.24</u> FAF: <u>FLUFY LOM</u> DIST FAF TO MAP: <u>3.59</u> THLD: <u>3.59</u>															
4. MIN. ALT: <u>FLUFY LOM 1500</u>															
5. DIST TO THLD FROM OM: <u>3.59</u> MM: <u>-</u> IM: <u>-</u> 150 HAT: <u>-</u> 100 HAT: <u>-</u> GS ANT: <u>923</u>															
6. MIN GS INCPT: <u>1500</u> GS ALT AT: <u>-</u> OM: <u>1490</u> MM: <u>-</u> IM: <u>-</u>															
7. GS ANGLE: <u>3.00</u> TCH: <u>50.0</u>															
8. MSA FROM: <u>LFK VORTAC 2400</u>															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 07	537	1/2	250	537	1/2	250	537	1/2	250	537	1/2	250			
S-LOC 07	680	1/2	393	680	1/2	393	680	5/8	393	680	5/8	393			
CIRCLING	740	1	444	760	1	464	880	1 1/2	584	1140	2 3/4	844			
NOTES: CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON LFK VORTAC AIRWAY RADIALS 245 CW 354. CHART NOTE: CIRCLING RWY 16, 25 NA AT NIGHT.															
CITY AND STATE LUFKIN, TX		ELEVATION: 296 TDZE: 287 AIRPORT NAME: ANGELINA COUNTY		FACILITY IDENTIFIER: I-LFK		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 7, AMDT 3 7 DECEMBER 2017						SUP: AMDT: 2B DATED 06/30/2011			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
21
CHECKED

CITY AND STATE
LUFKIN, TX

ELEVATION: 296 TDZE: 287
AIRPORT NAME:
ANGELINA COUNTY

FACILITY
IDENTIFIER:
I-LFK

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
ILS OR LOC RWY 7, AMDT 3
7 DECEMBER 2017

SUP:
AMDT: 2B
DATED: 06/30/2011