

U.S. DEPARTMENT of
TRANSPORTATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED

AT

☐

AA

☐

ALP

☐

AP

☐

AOP

☒

NBA

☒

OTHER (specify)

☒

ZAB, PRC FSS, LAX FPO, APT. MGR.

TAKEOFF MINIMUMS:

RWY 3, 11, 29: Standard

RWY 21: 1000-2 OR STD WITH MIN. CLIMB OF 360' PER NM TO 8400.

IFR DEPARTURE PROCEDURE:

RWY 3, 11: CLIMBING LEFT TURN TO 8400 VIA HEADING 360 BEFORE PROCEEDING ON COURSE.

RWY 21, 29: CLIMBING RIGHT TURN TO 8400 VIA HEADING 360 BEFORE PROCEEDING ON COURSE.



TAKEOFF OBSTACLES:

RWY 21 - 7959 TREE 340453/1092108
8792 TREE 340500/1092053
7942 TREE 340455/1092125

DEPARTURE OBSTACLES:

RWY 3, 11, 29 - 7810 TERRAIN 341016/1091410
RWY 21 - 7959 TREE 340453/1092108
8792 TREE 340500/1092053
7942 TREE 340455/1092125

*CONCURRENT WITH PUBLICATION OF KQ35 GPS RWY 21,
ORIGINAL

DEVELOPED BY		APPROVED BY	
SIGNATURE: 	DATE: 08/28/95 FIFO: AVN-140	SIGNATURE: 	DATE: 3/29/96 FIFO: AVN-140
CITY AND STATE SPRINGVILLE, AZ	AIRPORT SPRINGVILLE BABBITT FIELD	EFFECTIVE .	AMDT. NO. 0