

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33							Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW14 CLIMB TO 420 THEN CLIMBING RIGHT TURN TO 2500 DIRECT FELTI AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 150 SHIP 590157N/1615142W DISTANCE TO THLD FROM 250 HAT: 0.66 NM. CHART VDP AT 1.07 NM TO RW14* *LNAV ONLY. WAAS CHANNEL # 86640 REFERENCE PATH ID: W14A CHART CIRCLING ICON LTP HAE: 20.4 M						
OSE NDB		AKUWU (TF) (FB) (RNP 2.00)			168.88 / 88.71			3500								
TOG NDB/DME		AKUWU (TF) (FB) (RNP 2.00)			277.92 / 48.46			5000								
AKUWU (IAF)		FELTI (NOPT) (TF) (FB) (RNP 1.00)			193.93 / 8.52			2500								
FELTI (IF/IAF)		CAYRO (TF) (FB) (RNP 1.00)			143.72 / 5.75			1700								
CAYRO (FAF)		JEPRU/2.10 NM TO RW14 (TF) (FB) (RNP 0.30)			143.78 / 3.06											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD NW FELTI, LT, 143.72 INBOUND, 2500 FT. IN LIEU OF PT (IAF) 3. FAC: <u>143.78</u> FAF: <u>CAYRO</u> DIST FAF TO MAP: <u>5.16</u> THLD: <u>5.16</u> 4. MIN. ALT: <u>FELTI 2500, CAYRO 1700, JEPRU/2.10 NM TO RW14 720*</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: <u>1700</u> GS ALT AT: <u>CAYRO</u> OM: _____ MM: _____ IM: _____ 7. GS ANGLE: <u>3.00</u> TCH: <u>40.0</u> 34:1 IS CLEAR 8. MSA FROM: <u>RW14 3900</u>																
										MAG VAR: 11E			EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @							
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	268	1	250	268	1	250	268	1	250		NA					
LNAV/VNAV DA	321	1	303	321	1	303	321	1	303		NA					
LNAV MDA	400	1	382	400	1	382	400	1 1/8	382		NA					
CIRCLING	460	1	442	480	1	462	520	1 1/2	502		NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -20C (-4F) OR ABOVE 54C (130F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING TOGIAC ALTIMETER SETTING. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TOGIAC ALTIMETER SETTING: INCREASE LPV DA (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 18 TDZE: 18			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:				
PLATINUM, AK		AIRPORT NAME: PLATINUM						RNAV (GPS) RWY 14, AMDT 2, 08/17/2017				AMDT: 1A				
												DATED 01/13/2011				

QUALITY
 10
 CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
JEPRU/2.10 NM TO RW14	RW14 (MAP) (TF) (FO) (RNP 0.30)	143.78 / 2.10	
RW14 (MAP)	420 MSL (CA)	143.78	
420 MSL	FELTI (DF) (FO) (RNP 1.00)		2500

NOTES, (CONT.):

TO 371 FEET; INCREASE LNAV/VNAV DA TO 424 FEET AND ALL CATS VISIBILITIES 3/8 SM; INCREASE ALL MDA 120 FEET AND INCREASE LNAV AND CIRCLING CAT C VISIBILITY 1/4 SM.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON OSE NDB AIRWAY BEARINGS 292 CW 349.

QUALITY
10

CHECKED

CITY AND STATE

PLATINUM, AK

ELEVATION: 18

TDZE: 18

AIRPORT NAME:

PLATINUM

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 14, AMDT 2, 08/17/2017

SUP:

AMDT: 1A

DATED: 01/13/2011

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
10

CHECKED

CITY AND STATE PLATINUM, AK	ELEVATION: 18 AIRPORT NAME: PLATINUM	TDZE: 18	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 14, AMDT 2, 08/17/2017	SUP:
					AMDT: 1A
					DATED: 01/13/2011

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PAPM
RUNWAY	RW14
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W14A
LTP/FTP LATITUDE	590126.4800N
LTP/FTP LONGITUDE	1614958.1600W
LTP/FTP ELLIPSOIDAL HEIGHT	+00204
FPAP LATITUDE	590006.0255N
FPAP LONGITUDE	1614844.9280W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 318F1D3C

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00053
FPAP ORTHOMETRIC HEIGHT	+00053

QUALITY
10

CITY AND STATE PLATINUM, AK	ELEVATION: 18 AIRPORT NAME: PLATINUM	TDZE: 18	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 14, AMDT 2, 08/17/2017	SUP:	CHECKED
					AMDT:	1A
					DATED:	01/13/2011