

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
ATLANTA, TX	HALL-MILLER MUNI	9 FEB 2012	2

TAKEOFF MINIMUMS:

RWY 5, 200-1 ¼ OR STANDARD WITH MINIMUM CLIMB OF 229 FT PER NM TO 500
RWY 23, 300-1 ½

TEXTUAL DEPARTURE PROCEDURES:

RWY 5: CLIMB HEADING 048.11 TO 800 BEFORE TURNING LEFT.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 05, TOWER 4143 FT FROM DER, 677 FT LEFT OF CENTERLINE, UP TO 125 FT AGL/398 FT MSL.
NOTE: RWY 23, TREES BEGINNING 1042 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/489 FT MSL.

CONTROLLING OBSTACLES:

RWY 5: 429 FT MSL TREE 330707.00N/0941042.93W
RWY 23: 439 FT MSL TREE 330554.34N/0941210.53W; 489 FT MSL TREE 330525.99N/0941313.53W, 479 FT MSL TREE 330525.88N/0941325.16W
OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 05 – 625 FT MSL TOWER 330757.00N/0941021.00W

REMARKS:

