

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: RW16 CLIMB TO 13000 DIRECT IBBOR AND ON TRACK 254.72 TO HANIM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 13000. ADDITIONAL FLIGHT DATA: HOLD E, RT, 253.58 INBOUND. CHART FAS OBST: 3169 TREE 473444N/1140557W FAS OBST: 3438 AAO 473835N/1140543W DISTANCE TO THLD FROM 357 HATH: 0.99 NM. WAAS CHANNEL # 45814 REFERENCE PATH ID: W16A CHART MISSOULA ASOS-3 LTP HAE: 925.3 M											
HANIM	DMESR (FB)	012.49 / 23.36	7900												
ANGIL (IAF)	EGOCY (FB)	150.65 / 9.24	6700												
DMESR (IAF)	EGOCY (FB)	074.86 / 6.00	6700												
EGOCY (IF)	FATMI (FB)	164.97 / 6.74	5600												
FATMI (FAF)	GEDKE/4.00 NM TO RW16 (FB)	164.97 / 3.77													
GEDKE/4.00 NM TO RW16 (SEE FORM 8260-10)	RW16 (MAP) (FO)	164.97 / 4.00													
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT EGOCY _____ 3. FAC: 164.97 FAF: FATMI _____ DIST FAF TO MAP: 7.77 THLD: 7.77 4. MIN. ALT: EGOCY 6700, FATMI 5600, GEDKE/4.00 NM TO RW16 4400* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 5600 GS ALT AT: FATMI 5600 _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR 8. MSA FROM: RW16 11100				MAG VAR: 15E EPOCH YEAR: 2005											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A X												
CATEGORY =====>	A		B		C	D	E								
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	3443	1 1/4	357	3443	1 1/4	357	NA			NA					
LNAV/VNAV DA	3443	1 1/4	357	3443	1 1/4	357	NA			NA					
LNAV MDA	3800	1	714	3800	1	714	NA			NA					
CIRCLING	3800	1	714	3800	1	714	NA			NA					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. *LNAV ONLY CHART NOTE: USE MISSOULA ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA (SEE FORM 8260-10)															
CITY AND STATE RONAN, MT		ELEVATION: 3086 THRE: 3086 AIRPORT NAME: RONAN		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 1 18 OCTOBER 2012				SUP: AMDT: ORIG-A DATED 04/05/2012					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD

INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW16 (MAP)	3443 MSL	164.97	
3443 MSL	IBBOR (FB)		
IBBOR	HANIM (FO)	254.72 / 16.90	13000


NOTES, (CONT.):

CHART NOTE: CIRCLING NA E OF RWY 16-34

CHART NOTE: BARO-VNAV NA

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ANGIL ON V231 NORTHBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HANIM ON V120 WESTBOUND



CITY AND STATE

RONAN, MT

ELEVATION: 3086

THRE: 3086

AIRPORT NAME:

RONAN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 16, AMDT 1

18 OCTOBER 2012

SUP:

AMDT: ORIG-A

DATED: 04/05/2012

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER 7S0
RUNWAY RW16
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W16A
LTP/FTP LATITUDE 473425.5090N
LTP/FTP LONGITUDE 1140603.8810W
LTP/FTP ELLIPSOIDAL HEIGHT +09253
FPAP LATITUDE 473256.4600N
FPAP LONGITUDE 1140603.8100W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1288
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

2EA35777

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K1
LTP ORTHOMETRIC HEIGHT +09406
FPAP ORTHOMETRIC HEIGHT +09406

CITY AND STATE

RONAN, MT

ELEVATION: 3086

THRE: 3086

AIRPORT NAME:

RONAN

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 16, AMDT 1

18 OCTOBER 2012

SUP:

AMDT: ORIG-A

DATED: 04/05/2012

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP 7S0 K1FR16	AANGIL	010	ANGILK1EA0E	A	IF					18000		A	JS
SUSAP 7S0 K1FR16	AANGIL	020	EGOCYK1EA0EE	B	010TF		15070092	+	06700			A	JS
SUSAP 7S0 K1FR16	AHANIM	010	HANIMK1EA0E		IF					18000		A	JS
SUSAP 7S0 K1FR16	AHANIM	020	MESRK1EA0E	A	020TF		01250234	+	07900			A	JS
SUSAP 7S0 K1FR16	AHANIM	030	EGOCYK1EA0EE	B	010TF		07490060	+	06700			A	JS
SUSAP 7S0 K1FR16	R	010	EGOCYK1EA0E	I	IF			+	06700	18000		A	JS
SUSAP 7S0 K1FR16	R	020	FATMIK1EA1E	F	051TF		16500067	+	05600		RW16	K1PGA	JS
SUSAP 7S0 K1FR16	R	020	FATMIK1EA2	WALPV		ALNAV/VNAV	ALNAV						JS
SUSAP 7S0 K1FR16	R	021	GEDKEK1EA0E	S	031TF		16500038	V	0440004400		-300		A JS
SUSAP 7S0 K1FR16	R	030	RW16 K1PGGY	M	031TF		16500040		03126		-300		A JS
SUSAP 7S0 K1FR16	R	040		O	M	CA	1650	+	03443				A JS
SUSAP 7S0 K1FR16	R	050	IBBORK1EA0E		DF								A JS
SUSAP 7S0 K1FR16	R	060	HANIMK1EA0EY		010TF		2547	+	13000				A JS
SUSAP 7S0 K1FR16	R	070	HANIMK1EA0EE	R	HM		25360070	+	13000				A JS

[illegible][illegible]

CITY AND STATE RONAN, MT	ELEVATION: 3086 AIRPORT NAME: RONAN	THRE: 3086 RNAV	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 16, AMDT 1 18 OCTOBER 2012	SUP:
					AMDT: ORIG-A
					DATED: 04/05/2012

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE RONAN, MT	ELEVATION: 3086	THRE: 3086	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:	RONAN	RNAV	RNAV (GPS) RWY 16, AMDT 1	AMDT: ORIG-A
				18 OCTOBER 2012	DATED: 04/05/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ANGIL	ANGIL	010	IAF	IF		FB					
	ANGIL	EGOCY	020		TF		FB	1.0	150.7 (165.7T)	009.2	AA 06700	
	HANIM	HANIM	010		IF		FB					
	HANIM	DMESR	020	IAF	TF		FB	2.0	012.5 (027.5T)	023.4	AA 07900	
	HANIM	EGOCY	030		TF		FB	1.0	074.9 (089.9T)	006.0	AA 06700	
		EGOCY	010	FACF	IF		FB				AA 06700	
		FATMI	020	FAF	TF		FB	0.5	165.0 (180.0T)	006.7	AA 05600	
		GEDKE	021	SDF	TF		FB	0.3	165.0 (180.0T)	003.8	AA 04400 GS 04400	
		RW16	030	MAP	TF		FO	0.3	165.0 (180.0T)	004.0	AT 03126	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		165.0 (180.0T)		AA 03443	
	IBBOR	050		DF		FB					
	HANIM	060		TF		FO	1.0	254.7 (269.7T)		AA 13000	
	HANIM	070		HM	R	FO		253.6 (268.6T)	007.0	AA 13000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ANGIL	N475752.40	W1140928.49	N4757.873	W11409.475
	DMESR	N474854.96	W1141458.70	N4748.916	W11414.978
	EGOCY	N474855.49	W1140604.55	N4748.925	W11406.076
	FATMI	N474211.32	W1140604.24	N4742.189	W11406.071
	GEDKE	N473825.37	W1140604.07	N4738.423	W11406.068
	HANIM	N472813.27	W1143058.59	N4728.221	W11430.977
	IBBOR	N472820.86	W1140603.60	N4728.348	W11406.060
	RW16	N473425.51	W1140603.88	N4734.425	W11406.065

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW16	03086	40

CITY AND STATE
RONAN, MT

ELEVATION: 3086
AIRPORT NAME:

THRE: 3086
RONAN

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 16, AMDT 1
18 OCTOBER 2012

SUP:

AMDT: ORIG-A

DATED: 04/05/2012