

TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

(1) TAKEOFF MINIMUMS:

RWY 16, STANDARD WITH MINIMUM CLIMB OF 260 FT PER NM TO 9900 OR 6100-3 FOR CLIMB IN VISUAL CONDITIONS.

RWY 34, STANDARD WITH MINIMUM CLIMB OF 250 FT PER NM TO 9900 OR 6100-3 FOR CLIMB IN VISUAL CONDITIONS.

(2) TEXTUAL DEPARTURE PROCEDURE:

RWY 16 - CLIMB TO 8800 ON A HEADING BETWEEN 177 CW TO 336 FROM DEPARTURE END OF RUNWAY OR FOR CLIMB IN VISUAL CONDITIONS, CROSS RONAN AIRPORT AT OR ABOVE 9000 BEFORE PROCEEDING ON COURSE.

RWY 34 - CLIMB TO 8800 ON A HEADING BETWEEN 336 CCW TO 177 FROM DEPARTURE END OF RUNWAY OR FOR CLIMB IN VISUAL CONDITIONS, CROSS RONAN AIRPORT AT OR ABOVE 9000 BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES: NOTE: RWY 16, TREE 485 FEET FROM DER, 386 FEET LEFT OF CENTERLINE 50 FEET AGL/3149 FEET MSL.
NOTE: RWY 34, BUILDING 158 FEET FROM DER, 370 FEET LEFT OF CENTERLINE 40 FEET AGL/3130 FEET MSL. TREE 1358 FEET FROM DER, 556 FEET LEFT OF CENTERLINE 50 FEET AGL/3149 FEET MSL.

(4) CONTROLLING OBSTACLES:

RWY 16: 8196 MSL AAO 470927.80N/1142127.10W, 10020 MSL AAO 472255.50N/1135527.40W

RWY 34: 5674 MSL AAO 474625.00N/1141607.00W, 10020 MSL AAO 472255.50N/1135527.40W

VCOA: 10020 MSL AAO 472255.50N/1135527.40W

(5) City, State

RONAN, MT

(6) Airport

RONAN

(7) Effective Date

22 OCT 2009

(8) Amdt. No.

ORIG