

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION  
**TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.  
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
PLACERVILLE, CA	PLACERVILLE	15 NOVEMBER 2012	3

**TAKEOFF MINIMUMS:**

RWY 5: NA – OBSTACLES.  
RWY 23: STANDARD.

**TEXTUAL DEPARTURE PROCEDURES:**

RWY 23: CLIMB TO 5000 ON HNW R-226 THEN CLIMBING RIGHT TURN ON HNW R-276 TO HNW VOR/DME. AIRCRAFT DEPARTING HNW VOR/DME R-180 CW R-303 CLIMB ON COURSE; ALL OTHERS CLIMB IN HNW VOR/DME HOLDING PATTERN (HOLD SW, RT, 048.00 INBOUND) TO CROSS HNW VOR/DME AT OR ABOVE MEA/MCA FOR DIRECTION OF FLIGHT BEFORE PROCEEDING ON COURSE.

**TAKEOFF OBSTACLE NOTES:**

NOTE: RWY 23, HANGAR 20 FT FROM DER, 340 FT RIGHT OF CENTERLINE, 27 FT AGL/2586 FT MSL.

**CONTROLLING OBSTACLES:**

OBSTACLE MANDATING ODP ROUTE DEVELOPMENT: RWY 23 – 10,183 FT MSL AAO 385042.10N/1200931.60W.

