# U.S. DEPARTMENT of TRANSPORTATION FEDERAL AVIATION ADMINISTRATION

## TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks, and radials are magnetic. Elevations and attitudes are in feet, MSL. Attitudes are minimum attitudes unless otherwise indicated. Ceillings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

#### (1) TAKEOFF MINIMUMS:

RWY 10 STANDARD WITH MINIMUM CLIMB OF 400' PER NM TO 12200, OR 3200-3 FOR CLIMB IN VISUAL CONDITIONS. RWY 28 STANDARD WITH MINIMUM CLIMB OF 245' PER NM TO 9500, OR 3200-3 FOR CLIMB IN VISUAL CONDITIONS.

#### (2) TEXTUAL DEPARTURE PROCEDURE:

RWY 10 - CLIMB ON HEADING 146.81 TO 12200 BEFORE PROCEEDING ON COURSE.

RWY 28 - CLIMB ON HEADING 238.04 TO 9500 BEFORE PROCEEDING ON COURSE.

RWY 10/28 FOR CLIMB IN VISUAL CONDITIONS: CROSS YAMPA VALLEY AIRPORT AT OR ABOVE 9700 BEFORE PROCEEDING ON COURSE.

(3) TAKEOFF OBSTACLE NOTES: NOTE: RWY 10, TREE 241' FROM DER, 420' RIGHT OF CENTERLINE, 100' AGL/ 6699' MSL. TREE 644' FROM DER, 340' LEFT OF CENTERLINE, 100' AGL/ 6699' MSL. MULTIPLE TRANSMISSION TOWERS BEGINNING 3606' FROM DER, LEFT TO RIGHT OF CENTERLINE, UP TO 145' AGL/6745' MSL. TERRAIN BEGINNING 1714' FROM DER, 707' RIGHT OF CENTERLINE, UP TO 6676' MSL.

### (4) CONTROLLING OBSTACLES:

RWY 10: 8439 MSL AAO 402221.06N/1071232.64W, 12333 AAO 400453.70N/1070551.10W, 12554 AAO 400046.60N/1070502.90W.

RWY 28: 7199 MSL AAO 403047.75N/1071755.88W, 11048 AAO 400737.20N/1073154.50W, 12554 AAO 400046.60N/1070502.70W.

VCOA: 7919 MSL AAO 403336.12N/1071119.43W, 12333 AAO 400453.70N/1070551.10W.

(5) City, State

(A) Airport

YAMPA VALLEY

(7) Effective Date
02 JUL 2009

3