

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
UTUYE (IF/IAF)	ZOMOR (FB)	356.19 / 5.32	3600	LPV: DA LNAV/VNAV: DA LNAV: RW36 CLIMB TO 6000 DIRECT ZAVOV AND HOLD, CONTINUE CLIMB-IN-HOLD TO 6000. ADDITIONAL FLIGHT DATA: HOLD N, RT, 176.19 INBOUND. CHART FAS OBST: 2077 TRMSN TWR 391854N/0991733W CHART HILL CITY ASOS DISTANCE TO THLD FROM 291 HATH: 0.79 NM. WAAS CHANNEL # 40232 REFERENCE PATH ID: W36A CHART CIRCLING ICON LTP HAE: 583.5 M
ZOMOR (FAF)	WAJHU/2.10 NM TO RW36 (FB)	356.19 / 2.80	2680	
WAJHU/2.10 NM TO RW36	RW36 (MAP) (FO)	356.19 / 2.10		
RW36 (MAP)	2290 MSL	356.19		
2290 MSL	ZAVOV (FO)		6000	

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD S UTUYE, RT, 356.19 INBOUND, 4000 FT. IN LIEU OF PT (IAF)
- FAC: 356.19 FAF: ZOMOR DIST FAF TO MAP: 4.90 THLD: 4.90
- MIN. ALT: UTUYE 4000, ZOMOR 3600, WAJHU/2.10 NM TO RW36 2680*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 3600 GS ALT AT: ZOMOR 3600 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR
- MSA FROM:

MAG VAR: 5E EPOCH YEAR: 2010

MINIMUMS

TAKEOFF:				SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A		X							
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LPV DA	2290	1	291	2290	1	291	2290	1	291		NA								
LNAV/VNAV DA	2340	1 1/8	341	2340	1 1/8	341	2340	1 1/8	341		NA								
LNAV MDA	2420	1	421	2420	1	421	2420	1 1/4	421		NA								
CIRCLING	2460	1	461	2480	1	481	2500	1 1/2	501		NA								

NOTES:
 CHART NOTE: BARO-VNAV NA.
 CHART NOTE: USE HILL CITY ALTIMETER SETTING; WHEN NOT RECEIVED, USE HAYS ALTIMETER SETTING.
 CHART NOTE: CIRCLING NA WEST OF RWY 18-36.
 CHART NOTE: DME/DME RNP-0.3 NA.
 (SEE FORM 8260-10)

CITY AND STATE STOCKTON, KS	ELEVATION: 1999 THRE: 1999 AIRPORT NAME: ROOKS COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 12 DECEMBER 2013	SUP: AMDT: NONE DATED
---------------------------------------	---	--	--	------------------------------------

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: CIRCLING TO RWY 32 NA AT NIGHT.

*LNAV ONLY

TAA

	FROM	TO	ALT
1.	266/30 CW 086/30 266/9 CW 086/9 (NOPT)	266/9 CW 086/9 UTUVE (IF/IAF) (FB)	4200 4000
2.	086/30 CW 266/30 086/15 CW 266/15	086/15 CW 266/15 UTUVE (IAF) (FO)	4100 4000

CITY AND STATE
STOCKTON, KS

ELEVATION: 1999 THRE: 1999
AIRPORT NAME:
ROOKS COUNTY

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 36, ORIG
12 DECEMBER 2013

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KRCP
RUNWAY	RW36
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W36A
LTP/FTP LATITUDE	392023.0265N
LTP/FTP LONGITUDE	0991817.4040W
LTP/FTP ELLIPSOIDAL HEIGHT	+05835
FPAP LATITUDE	392152.1900N
FPAP LONGITUDE	0991815.0100W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1224
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

0BE5878B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+06093
FPAP ORTHOMETRIC HEIGHT	+06093

CITY AND STATE

STOCKTON, KS

ELEVATION: 1999

THRE: 1999

AIRPORT NAME:

ROOKS COUNTY

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 36, ORIG

12 DECEMBER 2013

SUP:

AMDT:

NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible][illegible][illegible]

QUALITY
CHECKED

CITY AND STATE STOCKTON, KS	ELEVATION: 1999	THRE: 1999	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 12 DECEMBER 2013	SUP:
	AIRPORT NAME: ROOKS COUNTY				AMDT: NONE
					DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	UTUVE	UTUVE	010	IAF	HF	R	FO		356.2 (001.2T)	005.0	AA 04000	
		UTUVE	010	FACF	IF		FB				AA 04000	
		ZOMOR	020	FAF	TF		FB	0.5	356.2 (001.2T)	005.3	AA 03600	
		WAJHU	021	SDF	TF		FB	0.3	356.2 (001.2T)	002.8	AA 02680	GS 02712
		RW36	030	MAP	TF		FO	0.3	356.2 (001.2T)	002.1	AT 02039	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		356.2 (001.2T)		AA 02290	
	ZAVOV	050		DF		FO				AA 06000	
	ZAVOV	060		HM	R	FO		176.2 (181.2T)	005.0	AA 06000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	UTUVE	N391009.39	W0991833.78	N3910.157	W09918.563
	WAJHU	N391816.95	W0991820.77	N3918.283	W09918.346
	ZAVOV	N393126.05	W0991759.62	N3931.434	W09917.994
	ZOMOR	N391528.72	W0991825.26	N3915.479	W09918.421
	RW36	N392023.03	W0991817.40	N3920.384	W09918.290

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW36	01999	40

QUALITY
CHECKED

CITY AND STATE STOCKTON, KS	ELEVATION: 1999	THRE: 1999	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 36, ORIG 12 DECEMBER 2013	SUP:
	AIRPORT NAME: ROOKS COUNTY				AMDT: NONE
					DATED: