

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

LNAV/VNAV ALL CATS VISIBILITY AND LNAV CAT C AND D VISIBILITY 1/8 MILE AND CIRCLING CAT C AND D VISIBILITY 1/4 MILE.

CHART NOTE: BARO-VNAV NA WITH WICHITA MID-CONTINENT ALTIMETER SETTING.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA

	FROM	TO	ALT
1.	115/30 CW 260/30 (NOPT)	115/6 CW 260/6	3200
2.	115/6 CW 260/6	DOLBE (IF/IAF) (FB)	3000
3.	260/30 CW 008/30	ILIBE (IAF) (FB)	3200
4.	008/30 CW 115/30	UJCEL (IAF) (FB)	4000

CITY AND STATE

WICHITA, KS

ELEVATION: 1409

THRE: 1409

AIRPORT NAME:

BEECH FACTORY

FACILITY IDENTIFIER:

RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:

RNAV (GPS) RWY 19, AMDT 1

25 JULY 2013

SUP: RNAV (GPS) RWY 18

AMDT: ORIG-A

DATED: 10/26/2006

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBEC
RUNWAY	RW19
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W19A
LTP/FTP LATITUDE	374216.8540N
LTP/FTP LONGITUDE	0971243.8105W
LTP/FTP ELLIPSOIDAL HEIGHT	+04005
FPAP LATITUDE	374049.4440N
FPAP LONGITUDE	0971306.2060W
THRESHOLD CROSSING HEIGHT (TCH)	00045.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0312
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 2CA7899D

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K3
LTP ORTHOMETRIC HEIGHT	+04293
FPAP ORTHOMETRIC HEIGHT	+04293

CITY AND STATE WICHITA, KS	ELEVATION: 1409 THRE: 1409	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP: RNAV (GPS) RWY 18
	AIRPORT NAME: BEECH FACTORY		RNAV (GPS) RWY 19, AMDT 1	AMDT: ORIG-A
			25 JULY 2013	DATED: 10/26/2006

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	DOLBE	DOLBE	010	IAF	HF	R	FO		187.5 (191.5T)	004.0	AA 03000	
	ILIBE	ILIBE	010	IAF	IF		FB					
	ILIBE	DOLBE	020		TF		FB	1.0	259.7 (263.7T)	008.9	AA 03000	
	UJCEL	UJCEL	010	IAF	IF		FB					
	UJCEL	DOLBE	020		TF		FB	1.0	115.4 (119.4T)	008.9	AA 03000	
		DOLBE	010	FACF	IF		FB				AA 03000	
		TOBEE	020	FAF	TF		FB	0.5	187.5 (191.5T)	006.2	AA 03000	
		WIBED	021	SDF	TF		FB	0.3	187.5 (191.5T)	003.4	AA 01920	GS 01931
		RW19	030	MAP	TF		FO	0.3	187.5 (191.5T)	001.5	AT 01454	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		187.5 (191.5T)		AA 01659	
	DENEY	050		DF		FO				AA 03000	
	DENEY	060		HM	R	FO		007.5 (011.5T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	DENEY	N373001.61	W0971551.64	N3730.027	W09715.861
	DOLBE	N375307.57	W0970956.64	N3753.126	W09709.944
	ILIBE	N375407.19	W0965846.23	N3754.120	W09658.771
	TOBEE	N374702.66	W0971130.48	N3747.044	W09711.508
	UJCEL	N375730.74	W0971944.07	N3757.512	W09719.735
	WIBED	N374345.14	W0971221.17	N3743.752	W09712.353
	RW19	N374216.85	W0971243.81	N3742.281	W09712.730

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW19	01409	45

CITY AND STATE
WICHITA, KS

ELEVATION: 1409 THRE: 1409
AIRPORT NAME:
BEECH FACTORY

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:
RNAV (GPS) RWY 18, AMDT 1
25 JULY 2013

SUP: RNAV (GPS) RWY 18
AMDT: ORIG-A
DATED: 10/26/2006