

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ICT VORTAC	CHITO OM/INT/RADAR	149.14 / 12.18	3500	LOC: 4.83 MILES AFTER CHITO OM/INT/RADAR ILS: DA CLIMB TO 3000 THEN CLIMBING LEFT TURN TO 3600 DIRECT ICT VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, LT, 180.00 INBOUND. CHART FAS OBST: 1438 T-L TWR 373306N/0972950W CHART IN PLANVIEW (CFBTF) AT 372934.69N/0973039.28W

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD S CHITO OM, LT, 016.00 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
3. FAC: 016.00 FAF: CHITO OM/INT/RADAR DIST FAF TO MAP: 4.83 THLD: 4.83
4. MIN. ALT: CHITO OM/INT/RADAR 3000
5. DIST TO THLD FROM OM: 4.83 MM: - IM: 961 150 HAT: 1834 100 HAT: 908 GS ANT: 1000
6. MIN GS INCPT: 3000 GS ALT AT: - OM: 2924 MM: - IM: 1415
7. GS ANGLE: 3.00 TCH: 52.3
8. MSA FROM: ICT VORTAC 4000

MAG VAR: 4E EPOCH YEAR: 2015

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			ILS: STANDARD #			LOC: STANDARD @		
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 01L	1514	1800	200	1514	1800	200	1514	1800	200	1514	1800	200	1514	1800	200
S-LOC 01L	1700	2400	386	1700	2400	386	1700	2400	386	1700	4000	386	1700	4000	386
CIRCLING	1800	1	467	1800	1	467	1800	1 1/2	467	1900	2	567	2000	2 1/4	667

NOTES:
 SA CATEGORY I ILS SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED S-ILS 1L: CAT A, B, C, D, RA 149, RVR 1400, HAT 150, DA 1464 MSL.
 CATEGORY II ILS SPECIAL AIRCREW AND AIRCRAFT CERTIFICATION REQUIRED S-ILS 1L: CAT A, B, C, D, RA 100, RVR 1200, HAT 100, DA 1414 MSL.
 (SEE FORM 8260-10)

CAT E 700-2 1/4
@ CAT E 800-2 1/4



CITY AND STATE WICHITA, KS	ELEVATION: 1333 TDZE: 1314	FACILITY IDENTIFIER: I-TWI	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 1L, AMDT 3C ILS RWY 1L (SA CAT I) ILS RWY 1L (CAT II) 11/13/2014	SUP:
	AIRPORT NAME: WICHITA DWIGHT D. EISENHOWER NATIONAL			AMDT: 3B
	DATED 04/05/2012			

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
ILS - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 1R.
 CHART NOTE: FOR INOPERATIVE ALSF-2, INCREASE S-ILS 1L CAT E VISIBILITY TO RVR 4000 AND S-LOC 1L CAT E VISIBILITY TO RVR 6000.
 SA CAT I CHART NOTE: REQUIRES SPECIFIC OPSPEC, MSPEC OR LOA APPROVAL AND USE OF HUD TO DH.

QUALITY
 7
 CHECKED

CITY AND STATE WICHITA, KS	ELEVATION: 1333 TDZE: 1314 AIRPORT NAME: WICHITA DWIGHT D. EISENHOWER NATIONAL	FACILITY IDENTIFIER: I-TWI	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 1L, AMDT 3C ILS RWY 1L (SA CAT I) ILS RWY 1L (CAT II) 11/13/2014	SUP:
				AMDT: 3B
				DATED: 04/05/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

ILS STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - ILS

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ICT	ICT	010		IF		FB					
	ICT	CHITO	020		TF		FO				AA 03500	
	ICT	CHITO	030	IAF	HF	L	FO		016.0 ()	T01.0	AA 03000	
		CFBTF	010	FACF	IF		FB				AA 03000 GI 03000	
		CHITO	020	FAF	CF		FB		016.0 ()	004.2	GI 03000 GS 02924	
		RW01L	030	MAP	CF		FO		016.0 ()	004.8	AT 01365	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		016.0 ()		AA 03000	
	ICT	050		DF		FO				AA 03600	
	ICT	060		HM	L	FO		180.0 ()	T01.0	AA 03600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ICT	N374442.92	W0973501.79	N3744.715	W09735.030
	CFBTF	N372934.69	W0973039.28	N3729.578	W09730.655
	CHITO	N373333.49	W0972850.21	N3733.558	W09728.837
	RW01L	N373806.07	W0972645.59	N3738.101	W09726.760
	ITWI (LOC)	N373951.34	W0972557.41	N3739.856	W09725.957

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW01L	01313	52

QUALITY
12
CHECKED

CITY AND STATE WICHITA, KS	ELEVATION: 1333 TDZE: 1314	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: WICHITA DWIGHT D. EISENHOWER NATIONAL	I-TWI	ILS OR LOC RWY 1L, AMDT 3C ILS RWY 1L (SA CAT I), ILS RWY 1L (CAT II)	AMDT: 3B
			11/13/2014	DATED: 04/05/2012

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

LOC STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICES - FAR PART 97.25

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - LOC

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	ICT	ICT	010		IF		FB					
	ICT	CHITO	020		TF		FO				AA 03500	
	ICT	CHITO	030	IAP	HF	L	FO		016.0()	T01.0	AA 03000	
		CFBTF	010	FACF	IF		FB				AA 03000	
		CHITO	020	FAF	CF		FB		016.0()	004.2	AA 03000	
		RW01L	030	MAP	CF		FO		016.0()	004.8	AT 01365	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		016.0()		AA 03000	
	ICT	050		DF		FO				AA 03600	
	ICT	060		HM	L	FO		180.0()	T01.0	AA 03600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ICT	N374442.92	W0973501.79	N3744.715	W09735.030
	CFBTF	N372934.69	W0973039.28	N3729.578	W09730.655
	CHITO	N373333.49	W0972850.21	N3733.558	W09728.837
	RW01L	N373806.07	W0972645.59	N3738.101	W09726.760
	ITWI (LOC)	N373951.34	W0972557.41	N3739.856	W09725.957

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW01L	01313	52

QUALITY
12
CHECKED

CITY AND STATE WICHITA, KS	ELEVATION: 1333	TDZE: 1314	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: WICHITA DWIGHT D. EISENHOWER NATIONAL		I-TWI	ILS OR LOC RWY 1L, AMDT 3C ILS RWY 1L (SA CAT I), ILS RWY 1L (CAT II)	AMDT: 3B
				11/13/2014	DATED: 04/05/2012