

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State	Airport	Effective Date	Amdt. No.
HARTFORD, KY	OHIO COUNTY	2 MAY 2013	1A

TAKEOFF MINIMUMS:

RWY 21: STANDARD.

RWY 3: 500 - 3 OR STANDARD WITH MINIMUM CLIMB OF 257 FEET PER NM TO 1200.

TEXTUAL DEPARTURE PROCEDURES:

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 3: TREES BEGINNING 388 FT FROM DER, 508 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/669 FT MSL. TREES BEGINNING 1741 FT FROM DER, 890 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/669 FT MSL. TOWER 2.5 NM FROM DER, 3516 FT RIGHT OF CENTERLINE, 290 FT AGL/950 FT MSL.

NOTE RWY 21: TREES BEGINNING 79 FT FROM DER, 294 FT RIGHT OF CENTERLINE, UP TO 100 FT AGL/585 FT MSL. TREES BEGINNING 95 FT FROM DER, 279 FT LEFT OF CENTERLINE, UP TO 100 FT AGL/568 FT MSL.

CONTROLLING OBSTACLES:

RWY 3: 950 FT MSL TOWER 372950.00N-0864851.00W.

