

PREPARED BY THE PRODUCT SUPPORT GROUP, AJV-34

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/22/13	AK	Toksook Bay	Toksook Bay	3/0100	7/15/13	Takeoff Minimums and (Obstacle) DP, Amdt 1

FDC **3/0100** OOK FI/P ODP TOKSOOK BAY, TOKSOOK BAY, AK. TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES AMDT 1... TAKEOFF MINIMUMS: RWY 16, STANDARD. RWY 34, STANDARD WITH MINIMUM CLIMB OF 481 FT PER NM TO 1700 OR 1600- 2 1/2 FOR CLIMB IN VISUAL CONDITIONS. TEXTUAL DEPARTURE PROCEDURE: RWY 16, CLIMB HEADING 165 TO 1000 BEFORE PROCEEDING ON COURSE. RWY 34, FOR CLIMB IN VISUAL CONDITIONS: CROSS TOKSOOK BAY AIRPORT AT OR ABOVE 1500 FT MSL BEFORE PROCEEDING ON COURSE. WHEN EXECUTING VCOA, NOTIFY ATC PRIOR TO DEPARTURE. NOTE: RWY 16, MULTIPLE LIGHTS BEGINNING AT DER, 40 FT LEFT OF CENTERLINE, UP TO 4 FT AGL/51 FT MSL. LIGHT 4 FT FROM DER, 78 FT RIGHT OF CENTERLINE 2 FT AGL/52 FT MSL. LIGHTS 50 FT FROM DER, 356 FT RIGHT OF CENTERLINE, 34 FT AGL/84 FT MSL. NOTE: RWY 34, MULTIPLE LIGHTS BEGINNING AT DER, 39 FT LEFT OF CENTERLINE, UP TO 3 FT AGL/74 FT MSL. MULTIPLE LIGHTS BEGINNING AT DER, 39 FT RIGHT OF CENTERLINE, UP TO 3 FT AGL/74 FT MSL. THIS IS TAKEOFF MINIMUMS AND (OBSTACLE) DEPARTURE PROCEDURES, AMDT 1A.