

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: 5.47 MILES AFTER VEALS LOM						
OCTOE INT		VEALS LOM		218.73 / 11.47				2600		CLIMBING LEFT TURN TO 2800 ON CMI VORTAC R-297 TO LODGE INT/CMI VORTAC 13.24 DME AND HOLD, OR AS DIRECTED BY ATC. ALTERNATE MA: CLIMB TO 2800 THEN CLIMBING LEFT TURN DIRECT VEALS LOM AND HOLD.						
CMI VORTAC		VEALS LOM		130.46 / 5.95				2600								
NEWMY INT (IF/IAF)		VEALS LOM		303.05 / 13.01				2600								
										ADDITIONAL FLIGHT DATA: HOLD NW, LT, 116.58 INBOUND. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD SE VEALS LOM, RT, 318.64 INBOUND. FAS OBST: 924 AAO 395845N/0881423W VEALS LOM TO RW32R: 3.09/54. CHART CIRCLING ICON. CHART: ASR						
1. PT <u>L</u> SIDE OF COURSE <u>138.64</u> OUTBOUND <u>2600</u> FT WITHIN <u>10</u> MILES OF <u>VEALS LOM</u> (IAF)																
2.																
3. FAC <u>318.64</u> FAF <u>VEALS LOM</u> DIST FAF TO MAP <u>5.47</u> THLD <u>5.47</u>																
4. MIN. ALT <u>VEALS LOM 2600</u>																
8. MSA FROM: <u>CM LOM 3000</u>																
MAG VAR: 3W EPOCH YEAR: 2015																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-32R	1240	4000	490	1240	4000	490	1240	4000	490	1240	6000	490				
CIRCLING	1240	1	485	1240	1	485	1500	2 1/4	745	1500	2 1/2	745				
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RANTOUL ALTIMETER SETTING AND INCREASE ALL MDA 60 FEET. INCREASE S-32R CAT C VISIBILITY TO RVR 5000 AND CAT D VISIBILITY TO 1 1/2 MILE.																
@ CAT C 800-2 1/4, CAT D 800-2 1/2 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.																
CITY AND STATE CHAMPAIGN/URBANA, IL		ELEVATION: 755 TDZE: 750 AIRPORT NAME: UNIVERSITY OF ILLINOIS-WILLARD		FACILITY IDENTIFIER: CM		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 32R, AMDT 11A 5 MARCH 2015				SUP						
										AMDT		11				
										DATE		05/07/2009				