

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
HUMUL	YABUN (FB)	137.88 / 7.95	2500	LPV: DA LNAV/VNAV: DA LNAV: RW20 CLIMB TO 3000 DIRECT JINUB AND ON TRACK 287.74 TO MCLEN AND HOLD.			
JILLY	HUGUD (FB)	242.14 / 11.29	2500				
MCLEN	RUNAE (FO)	045.36 / 20.66	2500	ADDITIONAL FLIGHT DATA: HOLD SW, RT, 036.67 INBOUND. FAS OBST: 1019 AAO 403229N/0885348W DISTANCE TO THLD FROM 250 HAT: 0.64 NM. CHART VDP AT 1.14 MILES TO RW20* *LNAV ONLY. WAAS CHANNEL # 99303 REFERENCE PATH ID: W20A CHART CIRCLING ICON. CHART APT ELEV 871. LTP HAE: 230.9 M			
YABUN (IAF)	RUNAE (NOPT) (FB)	110.89 / 5.00	2500				
HUGUD (IAF)	RUNAE (NOPT) (FB)	291.03 / 5.00	2500				
PNT VOR/DME (IAF)	RUNAE (NOPT) (FB)	208.13 / 10.71	2500				
RUNAE (IF/IAF)	UDIYO (FB)	200.96 / 6.10	2500				
(SEE FORM 8260-10)							

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. HOLD N RUNAE, RT, 200.96 INBOUND, 2500 FT. IN LIEU OF PT (IAF)	
3. FAC: <u>200.93</u> FAF: <u>UDIYO</u> DIST FAF TO MAP: <u>4.90</u> THLD: <u>4.90</u>	
4. MIN. ALT: <u>RUNAE 2500, UDIYO 2500</u>	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u>2500</u> GS ALT AT: <u>UDIYO 2500</u> OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u>3.00</u> TCH: <u>54.9</u> 34:1 IS CLEAR	
8. MSA FROM: <u>RW20 2800</u>	

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1121	2400	250	1121	2400	250	1121	2400	250	1121	2400	250			
LNAV/VNAV DA	1301	5000	430	1301	5000	430	1301	5000	430	1301	5000	430			
LNAV MDA	1280	2400	409	1280	2400	409	1280	4000	409	1280	4000	409			
CIRCLING	1340	1	469	1340	1	469	1620	2 1/4	749	1620	2 1/2	749			

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 54C (130F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: BARO-VNAV AND VDP NA WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING.

@ CAT C 800-2 1/4, CAT D 800-2 1/2
 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.

(SEE FORM 8260-10)

CITY AND STATE BLOOMINGTON/NORMAL, IL	ELEVATION: 871 TDZE: 871 AIRPORT NAME: CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1A 15 OCTOBER 2015	SUP: AMDT: 1 DATED 03/12/2009
--	---	------------------------------	---	-------------------------------------

QUALITY
A

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
UDIYO (FAF)	RW20 (MAP) (FO)	200.93 / 4.90	
RW20 (MAP)	1121 MSL	200.93	
1121 MSL	JINUB (FB)		
JINUB	MCLEN (FO)	287.74 / 8.61	3000

NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING: INCREASE ALL DA 116 FT AND ALL MDA 120 FT; INCREASE LPV ALL CATS VISIBILITY TO 3/4 MILE, LNAV/VNAV ALL CATS VISIBILITY TO 1 3/8 MILE, LNAV CATS C/D VISIBILITY TO 1 MILE, AND CIRCLING CATS C/D VISIBILITY 1/4 MILE.

CHART NOTE: FOR INOPERATIVE ALSF INCREASE LNAV CAT C/D VISIBILITY TO RVR 6000.

CHART NOTE: FOR INOPERATIVE ALSF-2 WHEN USING GENERAL DOWNING-PEORIA INTL ALTIMETER SETTING INCREASE LPV ALL CATS VISIBILITY TO RVR 6000.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT JILLY VIA V173 NORTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT PNT VOR/DME VIA V313 NORTH BOUND.

CITY AND STATE

BLOOMINGTON/NORMAL, IL

ELEVATION: 871

TDZE: 871

AIRPORT NAME:

CENTRAL IL RGNL ARPT AT BLOOMINGTON-
NORMAL

**FACILITY
IDENTIFIER:**

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 20, AMDT 1A

15 OCTOBER 2015

SUP:

AMDT:

1

DATED:

03/12/2009



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE
BLOOMINGTON/NORMAL, IL

ELEVATION: 871 TDZE: 871
AIRPORT NAME:
CENTRAL IL RGNL ARPT AT BLOOMINGTON-
NORMAL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 20, AMDT 1A
15 OCTOBER 2015

SUP:
AMDT: 1
DATED: 03/12/2009

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KBMI
RUNWAY RW20
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W20A
LTP/FTP LATITUDE 402905.8015N
LTP/FTP LONGITUDE 0885425.8625W
LTP/FTP ELLIPSOIDAL HEIGHT +02309
FPAP LATITUDE 402740.9600N
FPAP LONGITUDE 0885501.7600W
THRESHOLD CROSSING HEIGHT (TCH) 00054.9
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 0312
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

CB84ECFE

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +02629
FPAP ORTHOMETRIC HEIGHT +02629

CITY AND STATE BLOOMINGTON/NORMAL, IL	ELEVATION: 871 TDZE: 871 AIRPORT NAME: CENTRAL IL RGNL ARPT AT BLOOMINGTON- NORMAL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1A 15 OCTOBER 2015	SUP:
				AMDT: 1
				DATED: 03/12/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	HUMUL	HUMUL	010		IF		FB					
	HUMUL	YABUN	020	IAF	TF		FB	2.0	137.9 (134.9T)	008.0	AA 02500	
	HUMUL	RUNAE	030		TF		FB	1.0	110.9 (107.9T)	005.0	AA 02500	
	JILLY	JILLY	010		IF		FB					
	JILLY	HUGUD	020	IAF	TF		FB	2.0	242.1 (239.1T)	011.3	AA 02500	
	JILLY	RUNAE	030		TF		FB	1.0	291.0 (288.0T)	005.0	AA 02500	
	MCLLEN	MCLLEN	010		IF		FB					
	MCLLEN	RUNAE	020		TF		FO	2.0	045.4 (042.4T)	020.7	AA 02500	
	MCLLEN	RUNAE	030	IAF	HF	R	FO		201.0 (198.0T)	004.0	AA 02500	
	PNT	PNT	010	IAF	IF		FB					
	PNT	RUNAE	020		TF		FB	1.0	208.1 (205.1T)	010.7	AA 02500	
		RUNAE	010	FACF	IF		FB				AA 02500	
		UDIYO	020	FAF	TF		FB	0.5	201.0 (198.0T)	006.1	AA 02500	
		RW20	030	MAP	TF		FO	0.3	200.9 (197.9T)	004.9	AT 00917	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		200.9 (197.9T)		AA 01121	
	JINUB	050		DF		FB					
	MCLLEN	060		TF		FO	1.0	287.7 (284.7T)		AA 03000	
	MCLLEN	070		HM	R	FO		036.7 (033.7T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	PNT	N404916.32	W0884400.63	N4049.272	W08844.011
	HUGUD	N403801.41	W0884344.32	N4038.024	W08843.739
	HUMUL	N404643.39	W0890338.37	N4046.723	W08903.640
	JILLY	N404349.90	W0883100.23	N4043.832	W08831.004
	JINUB	N402207.93	W0885722.38	N4022.132	W08857.373
	MCLLEN	N402418.98	W0890816.55	N4024.316	W08908.276
	RUNAE	N403934.15	W0884959.17	N4039.569	W08849.986
	UDIYO	N403345.89	W0885227.16	N4033.765	W08852.453
	YABUN	N404106.55	W0885614.30	N4041.109	W08856.238
	RW20	N402905.80	W0885425.86	N4029.097	W08854.431

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW20	00863	55

QUALITY
CHECKED

CITY AND STATE BLOOMINGTON/NORMAL, IL	ELEVATION: 871	TDZE: 871	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 20, AMDT 1A 15 OCTOBER 2015	SUP:
	AIRPORT NAME: CENTRAL IL RGNL ARPT AT BLOOMINGTON-NORMAL				AMDT: 1
					DATED: 03/12/2009