

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
 VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
LVZ VORTAC (IF/IAF)	ZOGBA/LVZ 8.20 DME	080.04 / 8.20	3800	MAP: XETUW/LVZ 12.98 DME CLIMBING LEFT TURN TO 4000 DIRECT LVZ VORTAC AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 010.00 INBOUND. FAS OBST: 2259 AAO 411908N/0752626W FAC CROSSES MID POINT OF RWY 5-23. CHART CIRCLING ICON. CHART MOUNT POCONON ASOS.

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT LVZ VORTAC
3. FAC 080.04 FAF ZOGBA/LVZ 8.20 DME DIST FAF TO MAP THLD
4. MIN. ALT LVZ VORTAC 4000, ZOGBA 3800
8. MSA FROM: LVZ VORTAC 4000

MAG VAR: 10W EPOCH YEAR: 1965

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N	A	X							
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
CIRCLING	2600	1 1/4	871	2620	1 1/4	891		NA			NA					

NOTES:

CHART NOTE: PROCEDURE NA AT NIGHT.
 CHART NOTE: USE MOUNT POCONO ALTIMETER SETTING; WHEN NOT RECEIVED, USE WILKES-BARRE/SCRANTON ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET AND CAT B CIRCLING VISIBILITY 1/4 MILE.
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON LVZ VORTAC AIRWAY RADIALS 047 CW 124.



CITY AND STATE STERLING, PA	ELEVATION: 1729	TDZE:	FACILITY IDENTIFIER: LVZ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME-B, ORIG 17 OCTOBER 2013	SUP	
	AIRPORT NAME: SPRING HILL				AMDT	NONE
					DATE	