

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HATH, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW10R CLIMB TO 480 THEN CLIMBING RIGHT TURN TO 2000 DIRECT ANGEER AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 311.60 INBOUND. CHART FAS OBST: 120 TREE 272919N/0802410W CHART W497B. DISTANCE TO THLD FROM 250 HAT: 0.63 NM. CHART VDP AT 0.96 NM TO RW10R* *LNAV ONLY. WAAS CHANNEL # 69529 REFERENCE PATH ID: W10A CHART CIRCLING ICON. LTP HAE: -20.5 M									
TRV VORTAC		MIMBE (TF) (FB) (RNP 2.00)		238.69 / 7.70				2000											
SHEDS		HASOK (TF) (FB) (RNP 2.00)		353.22 / 6.08				2000											
MIMBE (IAF)		ZAHZA (TF) (FB) (RNP 1.00)		182.37 / 6.00				2000											
HASOK (IAF)		ZAHZA (TF) (FB) (RNP 1.00)		017.36 / 6.00				2000											
ZAHZA (IF)		TIKIY (TF) (FB) (RNP 1.00)		097.37 / 6.02				1800											
(SEE FORM 8260-10)																			
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT ZAHZA 3. FAC: 097.42 FAF: TIKIY DIST FAF TO MAP: 5.43 THLD: 5.43 4. MIN. ALT: ZAHZA 2000, TIKIY 1800, SIVYO/2.00 NM TO RW10R 700* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 1800 GS ALT AT: TIKIY 1800 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.00 TCH: 48.6 34:1 IS CLEAR 8. MSA FROM: RW10R 2600																MAG VAR: 7W		EPOCH YEAR: 2015	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY =====>		A		B		C		D		E									
	DH/MDA	VIS	HATH/HAA	DH/MDA	VIS	HATH/HAA	DH/MDA	VIS	HATH/HAA	DH/MDA	VIS	HATH/HAA	DH/MDA	VIS	HATH/HAA				
LPV DA	273	3/4	250	273	3/4	250	273	3/4	250	273	3/4	250							
LNAV/VNAV DA	348	1	325	348	1	325	348	1	325	348	1	325							
LNAV MDA	380	1	357	380	1	357	380	1	357	380	1	357							
CIRCLING	460	1	437	480	1	457	880	2 1/2	857	880	2 3/4	857							
NOTES: CHART NOTE: BARO-VNAV NA WHEN USING VERO BEACH ALTIMETER SETTING. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -1C (31F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART SPEED ICON IN PLANVIEW AT MIMBE : MAX 210 KIAS. (CONTINUED ON PAGE 2)																			
CITY AND STATE FORT PIERCE, FL		ELEVATION: 23 TDZE: 23 AIRPORT NAME: TREASURE COAST INTL		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10R, AMDT 2C 2 MARCH 2017						SUP:							
												AMDT:		2B					
												DATED		06/23/2016					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HATH, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
TIKIY (FAF)	SIVYO/2.00 NM TO RW10R (TF) (FB) (RNP 0.30)	097.42 / 3.43	
SIVYO/2.00 NM TO RW10R	RW10R (MAP) (TF) (FO) (RNP 0.30)	097.42 / 2.00	
RW10R (MAP)	480 MSL	097.42	480
480 MSL	ANGEE (DF) (FO) (RNP 1.00)		2000

NOTES, (CONT.):

CHART SPEED ICON IN PLANVIEW AT HASOK : MAX 210 KIAS.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SHEDS ON V531 SOUTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVAL ON TRV VORTAC AIRWAY RADIALS 150 CW 325.

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: VDP NA WITH VERO BEACH ALTIMETER SETTING.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE VERO BEACH ALTIMETER SETTING AND INCREASE ALL DA 23 FEET AND ALL MDA 40 FEET; INCREASE LPV ALL CATS, LNAV/VNAV ALL CATS AND LNAV CATS C/D VISIBILITY 1/8 MILE, AND INCREASE CIRCLING CAT C/D VISIBILITY 1/4 MILE.

CITY AND STATE FORT PIERCE, FL	ELEVATION: 23 AIRPORT NAME: TREASURE COAST INTL	TDZE: 23 RNAV	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10R, AMDT 2C 2 MARCH 2017	SUP:
					AMDT: 2B
					DATED: 06/23/2016

QUALITY
18
CHECKED

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HATh, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KFPR
RUNWAY	RW10R
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W10A
LTP/FTP LATITUDE	272950.1160N
LTP/FTP LONGITUDE	0802245.7540W
LTP/FTP ELLIPSOIDAL HEIGHT	-00205
FPAP LATITUDE	272949.3740N
FPAP LONGITUDE	0802105.5625W
THRESHOLD CROSSING HEIGHT (TCH)	00048.6
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0768
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 B111604B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K7
LTP ORTHOMETRIC HEIGHT	+00070
FPAP ORTHOMETRIC HEIGHT	+00070

CITY AND STATE

FORT PIERCE, FL

ELEVATION: 23

TDZE: 23

AIRPORT NAME:

TREASURE COAST INTL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 10R, AMDT 2C

2 MARCH 2017

SUP:

AMDT:

DATED: 06/23/2016

QUALITY
18
CHECKED