

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW08 CLIMBING LEFT TURN TO 9000 DIRECT BVL VORTAC AND HOLD, CONTINUE CLIMB-IN-HOLD TO 9000. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 247.16 INBOUND. FAS OBST: 4843 AAO 404400N/1140830W CHART LUCIN A MOA. CHART LUCIN C MOA. CHART R-6404A. CHART R-6404B & D. CHART R-6404C. CHART R-6405. CHART R-6406A. CHART CIRCLING ICON. JURGA TO RW08: 6.63/40 4869 AAO 404403N/1141003W. 7491 AAO 404412N/1141603W.											
UHEPI (IF/IAF)	VITHE (FB)	082.45 / 4.99	9800												
VITHE (FAF)	JURGA/5.42 NM TO RW08 (FB)	082.96 / 4.58													
JURGA/5.42 NM TO RW08	RW08 (MAP) (FO)	082.96 / 5.42													
RW08 (MAP)	4637 MSL	082.96	9000												
4637 MSL	BONNEVILLE VORTAC (FO)														
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. PROFILE STARTS AT UHEPI 3. FAC: <u>082.96</u> FAF: <u>VITHE</u> DIST FAF TO MAP: <u>10.00</u> THLD: _____ 4. MIN. ALT: <u>UHEPI 11000, VITHE 9800, JURGA/5.42 NM TO RW08 8100</u> 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____ 7. GS ANGLE: _____ TCH: _____ 8. MSA FROM: <u>RW08 12000</u>				MAG VAR: <u>12E</u> EPOCH YEAR: <u>2015</u>											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		@									
CATEGORY ==>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	6100	1 1/4	1863	6100	1 1/2	1863	6100	3	1863	6100	3	1863	6100	3	1863
NOTES: CHART NOTE: CIRCLING NA NORTH OF RWY 8-26. CHART NOTE: DME/DME RNP-0.3 NA. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT UHEPI ON V32 WESTBOUND.								@ CAT A, B 1900-2, CAT C, D, E 1900-3 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.							
CITY AND STATE		ELEVATION: 4237 TDZE:		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:		SUP:							
WENDOVER, UT		AIRPORT NAME:		RNAV		RNAV (GPS)-A, AMDT 1 13 NOVEMBER 2014		AMDT: ORIG							
		WENDOVER						DATED 11/30/2000							

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KENVK2FRNV-A	R	010UHEPIK2EA0E	I	IF				+ 11000	18000			B JC
SUSAP	KENVK2FRNV-A	R	020VITHEK2EA0E	F	051TF		08250050		+ 09800		RW08	K2PGB	JC
SUSAP	KENVK2FRNV-A	R	021JURGAK2EA0E	S	031TF		08300046	V	0810008100		-663		B JC
SUSAP	KENVK2FRNV-A	R	030RW08	K2PGOGY	M	031TF			04270		-663		B JC
SUSAP	KENVK2FRNV-A	R	040		0 M	CA		0830		+ 04637			B JC
SUSAP	KENVK2FRNV-A	R	050BVL	K2D	0VY	L	DF			+ 09000			B JC
SUSAP	KENVK2FRNV-A	R	060BVL	K2D	0VE	R	HM		24720070		+ 09000		B JC

[illegible][illegible]

CITY AND STATE WENDOVER, UT	ELEVATION: 4237 AIRPORT NAME: WENDOVER	TDZE: RNAV	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, AMDT 1 13 NOVEMBER 2014	SUP:
					AMDT: ORIG
					DATED: 11/30/2000

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		UHEPI	010	FACF	IF		FB				AA 11000	
		VITHE	020	FAF	TF		FB	0.5	082.5(094.5T)	005.0	AA 09800	
		JURGA	021	SDF	TF		FB	0.3	083.0(095.0T)	004.6	AA 08100 GS 08100	
		RW08	030	MAP	TF		FO	0.3	083.0(095.0T)	005.4	AT 04270	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		083.0(095.0T)		AA 04637	
	BVL	050		DF	L	FO				AA 09000	
	BVL	060		HM	R	FO		247.2(259.2T)	007.0	AA 09000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	BVL	N404333.95	W1134526.70	N4043.566	W11345.445
	JURGA	N404336.90	W1140942.37	N4043.615	W11409.706
	UHEPI	N404424.28	W1142215.65	N4044.405	W11422.261
	VITHE	N404400.83	W1141542.69	N4044.014	W11415.712
	RW08	N404308.19	W1140236.33	N4043.137	W11402.606

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW08	04230	40



CITY AND STATE WENDOVER, UT	ELEVATION: 4237	TDZE:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME:			RNAV (GPS)-A, AMDT 1	AMDT: ORIG
	WENDOVER		RNAV	13 NOVEMBER 2014	DATED: 11/30/2000