

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE,
TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: DA			
ZUREK (IAF)	WOLKA (TF) (FB) (RNP 1.00)	315.21 / 4.00	5000	CLIMB TO 3000 ON TRACK 315.06 TO HODAX AND ON TRACK 306.22 TO KAGLE AND HOLD.			
WOLKA (IF)	NKORT (TF) (FB) (RNP 1.00)	315.18 / 7.40	3000				
NKORT	TARRO (TF) (FB) (RNP 1.00)	315.13 / 3.92	2400	ADDITIONAL FLIGHT DATA: HOLD NW, RT, 126.00 INBOUND. DISTANCE TO THLD FROM 370 HAT: 0.99 NM. ROUTE TYPE: A,H ROUTE TYPE QUALIFIER 2: S ROUTE TYPE QUALIFIER 1: F #TCH 631.1 MSL (DO NOT CHART)			
TARRO (FAF)	RW31L (MAP) (TF) (FO)	315.10 / 5.55					
RW31L (MAP)	HODAX (TF) (FB) (RNP 1.00)	315.06 / 6.72					
HODAX	KAGLE (TF) (FO) (RNP 1.00)	306.22 / 26.04	3000				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. PROFILE STARTS AT ZUREK	
3. FAC: <u>315.10</u> FAF: <u> </u> DIST FAF TO MAP: <u> </u> THLD: <u> </u>	
4. MIN. ALT: ZUREK 5000, WOLKA 5000, NKORT 3000, TARRO 2400	
5. DIST TO THLD FROM OM: <u>5.55</u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u>2400</u> GS ALT AT: TARRO 2400 OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u>3.00</u> TCH: <u>54.0#</u> 34:1 IS NOT CLEAR	
8. MSA FROM: RW31L 3600	

MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA

AUTHORIZATION REQUIRED															
RNP 0.30 DA	951	6000	370	951	6000	370	951	6000	370	951	6000	370			

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, PROCEDURE NA BELOW -4C (25F) OR ABOVE 54C (130F).
 CHART NOTE: SIMULTANEOUS APPROACH AUTHORIZED WITH RWY 31R.
 CHART NOTE: GPS REQUIRED.
 CHART PLANVIEW NOTE: RADAR REQUIRED.
 (SEE FORM 8260-10)

CITY AND STATE DALLAS-FORT WORTH, TX	ELEVATION: 607 TDZE: 581	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 31L, AMDT 1B 18 SEPTEMBER 2014	SUP:
				AMDT: 1A
				DATED 02/06/2014

QUALITY
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) - STANDARD,
INSTRUMENT APPROACH PROCEDURE, - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT.

CHART NOTE: USE OF FD OR AP PROVIDING RNAV TRACK GUIDANCE REQUIRED DURING SIMULTANEOUS OPERATIONS.



CITY AND STATE DALLAS-FORT WORTH, TX	ELEVATION: 607	TDZE: 581	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (RNP) Z RWY 31L, AMDT 1B 18 SEPTEMBER 2014	SUP:
	AIRPORT NAME:				AMDT: 1A
	DALLAS/FORT WORTH INTL				DATED: 02/06/2014

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KDFWK4FH31LZ	AZUREK	010ZUREKK4PC0E	A	IF				+ 05000	18000		A FS	
SUSAP	KDFWK4FH31LZ	AZUREK	020WOLKAK4PC0E	B	010TF				+ 05000			A FS	
SUSAP	KDFWK4FH31LZ	AZUREK	030NKORTK4PC0EE		010TF				+ 03000			A FS	
SUSAP	KDFWK4FH31LZ	H	010NKORTK4PC0E	I	IF				+ 03000	18000		A FS	
SUSAP	KDFWK4FH31LZ	H	020TARROK4PC1E	F	010TF				+ 02400		RW31L K4PGA	FS	
SUSAP	KDFWK4FH31LZ	H	020TARROK4PC2W					A031				FS	
SUSAP	KDFWK4FH31LZ	H	030RW31LK4PG0GY	M	031TF			00631		-300		A FS	
SUSAP	KDFWK4FH31LZ	H	040HODAXK4PC0E	M	010TF							A FS	
SUSAP	KDFWK4FH31LZ	H	050KAGLEK4PC0EY		010TF				+ 03000			A FS	
SUSAP	KDFWK4FH31LZ	H	060KAGLEK4PC0EE	R	HM		12600040		+ 03000			A FS	

[illegible][illegible]

QUALITY
2
CHECKED

CITY AND STATE DALLAS-FORT WORTH, TX	ELEVATION: 607 TDZE: 581	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: DALLAS/FORT WORTH INTL	RNAV	RNAV (RNP) Z RWY 31L, AMDT 1B	AMDT: 1A
			18 SEPTEMBER 2014	DATED: 02/06/2014

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (RNP) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (RNP)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ZUREK	ZUREK	010	IAF	IF		FB				AA 05000	
	ZUREK	WOLKA	020		TF		FB	1.0			AA 05000	
	ZUREK	NKORT	030		TF		FB	1.0			AA 03000	
		NKORT	010	FACF	IF		FB				AA 03000	
		TARRO	020	FAF	TF		FB	1.0			AA 02400	
		RW31L	030	MAP	TF		FO	0.3			AT 00631	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	HODAX	040		TF		FB	1.0				
	KAGLE	050		TF		FO	1.0			AA 03000	
	KAGLE	060		HM	R	FO		126.0 (130.0T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HODAX	N325830.21	W0970902.13	N3258.504	W09709.036
	KAGLE	N331518.70	W0973244.51	N3315.312	W09732.742
	NKORT	N324614.69	W0965626.22	N3246.245	W09656.437
	TARRO	N324912.65	W0965928.65	N3249.211	W09659.478
	WOLKA	N324038.35	W0965042.19	N3240.639	W09650.703
	ZUREK	N323736.14	W0964736.22	N3237.602	W09647.604
	RW31L	N325324.97	W0970347.79	N3253.416	W09703.797

RUNWAY DATA	RWY	THRESHOLD	TCH
		ELEVATION	
	RW31L	00577	54

QUALITY
2
CHECKED

CITY AND STATE DALLAS-FORT WORTH, TX	ELEVATION: 607	TDZE: 581	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (RNP) Z RWY 31L, AMDT 1B 18 SEPTEMBER 2014	SUP:
	AIRPORT NAME: DALLAS/FORT WORTH INTL				AMDT: 1A
					DATED: 02/06/2014