U.S. DEPARTMENT of TRANSPORTATION FEDERAL AVIATION ADMINISTRATION DE	PARTURE PROCEDURES / TAKEOFF MINIMUMS
Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.	
OORDINATED WITH:  ATA AAT ALPA APA AOPA NBA  X X X	
AKEOFF MINIMUMS:	
WY 03: STANDARD	
WY 21: STANDARD	
TO DEDARTINE PROCEDURE.	
R DEPARTURE PROCEDURE:	
WY 21: TURN LEFT,	
RCRAFT DEPARTING FLG VOR/DME R-160 CW R-175 CLIMI LIMB SOUTHBOUND ON FLG R-172 TO 9000, THEN CLIMBII RECT FLG VOR/DME.	
OTE: 7075 TREES AT DEPARTURE END OF RWY 21 AND R	WY 03.
AKEOFF OBSTACLES:	DEPARTURE OBSTACLES:
	RWY 03: 9399 TOWER 351430/1113610 RWY 21: 8045 TOWER 350845/1114505

## DEVELOPED BY APPROVĘD BY SIGNATURE DATE: OCT 2 3 1992 SIGNATURE: 5 DATE: 10/20/92 SCOTT THOMPSON JOHN D. PEARSANL JR. FIFO: SAC FIFO: SAC CITY AND STATE AIRPORT EFFECTIVE DATE AMDT. NO. ROUTINE 2 FLAGSTAFF, AZ PULLIAM