

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LPV: DA LNAV/VNAV: DA LNAV: UYASI CLIMB TO 2600 DIRECT HOBUV AND HOLD. ADDITIONAL FLIGHT DATA: HOLD NE, RT, 223.84 INBOUND. FAS OBST: 1021 AAO 345811N/0923640W DISTANCE TO THLD FROM 307 HAT: 0.84 NM. WAAS CHANNEL # 97338 REFERENCE PATH ID: W04A CHART CIRCLING ICON FAC CROSSES RWY C/L EXTENDED 3992 FROM THLD. CHART PLANVIEW NOTE: FINAL APPROACH COURSE OFFSET 3.00 DEGREES. FTP HAE: 55.8 M											
VAKUY (IF/IAF)	YUDUT (FB)	046.64 / 6.00	2100												
YUDUT (FAF)	UYASI (MAP) (FO)	046.69 / 4.95	2600												
UYASI (MAP)	583 MSL	046.69													
583 MSL	HOBUV (FO)														
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SW VAKUY, RT, 046.64 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 046.69 FAF: YUDUT DIST FAF TO MAP: 4.95 THLD: 5.61 4. MIN. ALT: VAKUY 3000, YUDUT 2100 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: 2100 GS ALT AT: YUDUT 2100 OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: 3.00 TCH: 40.0 34:1 IS CLEAR 8. MSA FROM: <u> </u>				MAG VAR: 1E EPOCH YEAR: 2015											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY =====>	A		B		C		D		E						
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	583	1	307	583	1	307	583	1	307	583	1	307			
LNAV/VNAV DA	658	1 1/4	382	658	1 1/4	382	658	1 1/4	382	658	1 1/4	382			
LNAV MDA	1340	1 1/4	1064	1340	1 1/2	1064	1340	3	1064	1340	3	1064			
CIRCLING	1340	1 1/4	1064	1340	1 1/2	1064	1340	3	1064	1380	3	1104			
NOTES: CHART NOTE: BARO-VNAV NA. CHART NOTE: USE BILL AND HILLARY CLINTON NATIONAL/ADAMS FIELD ALTIMETER SETTING; WHEN NOT RECEIVED, PROCEDURE NA. CHART NOTE: DME/DME RNP-0.3 NA.															
CITY AND STATE CONWAY, AR		ELEVATION: 276 TDZE: 276 AIRPORT NAME: CANTRELL FIELD		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 13 NOVEMBER 2014				SUP: AMDT: NONE DATED					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA	FROM	TO	ALT
1.	317/30 CW 137/30 (NOPT)	317/8 CW 137/8	3400
	317/8 CW 137/8	VAKUY (IF/IAF) (FB)	3000
2.	137/30 CW 317/30	137/10 CW 317/10	3300
	137/10 CW 317/10	VAKUY (IF/IAF) (FO)	3000

QUALITY
6
CHECKED

CITY AND STATE CONWAY, AR	ELEVATION: 276 TDZE: 276 AIRPORT NAME: CANTRELL FIELD	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG 13 NOVEMBER 2014	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCXW
RUNWAY	RW04
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	0
REFERENCE PATH DATA SELECTOR	W04A
REFERENCE PATH IDENTIFIER (APPROACH ID)	350050.7145N
FTP LATITUDE	0923339.9640W
FTP LONGITUDE	+00558
FTP ELLIPSOIDAL HEIGHT	350150.7225N
FPAP LATITUDE	0923219.6655W
FPAP LONGITUDE	00040.0
THRESHOLD CROSSING HEIGHT (TCH)	F
TCH UNITS SELECTOR (METERS OR FEET USED)	03.00
GLIDEPATH ANGLE (GPA)	106.75
COURSE WIDTH AT THRESHOLD	0000
LENGTH OFFSET	40.0
HORIZONTAL ALERT LIMIT (HAL)	50.0
VERTICAL ALERT LIMIT (VAL)	

CRC REMAINDER

19A8B314

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00838
FPAP ORTHOMETRIC HEIGHT	+00838



CITY AND STATE

CONWAY, AR

ELEVATION: 276

TDZE: 276

AIRPORT NAME:

CANTRELL FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, ORIG

13 NOVEMBER 2014

SUP:

AMDT: NONE

DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
6
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated) Page 4 of 5 Pages

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	VAKUY	VAKUY	010	IAF	HF	R	FO		046.6 (047.6T)	004.0	AA 03000	
		VAKUY	010	FACF	IF		FB				AA 03000	
		YUDUT	020	FAF	TF		FB	0.5	046.6 (047.6T)	006.0	AA 02100	
		UYASI	030	MAP	TF		FO	0.3	046.7 (047.7T)	005.0	AT 00524	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		046.7 (047.7T)		AA 00583	
	HOBVU	050		DF		FO				AA 02600	
	HOBVU	060		HM	R	FO		223.8 (224.8T)	004.0	AA 02600	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HOBVU	N350918.88	W0922329.78	N3509.315	W09223.496
	UYASI	N350024.20	W0923415.43	N3500.403	W09234.257
	VAKUY	N345301.21	W0924406.41	N3453.020	W09244.107
	YUDUT	N345704.05	W0923842.80	N3457.068	W09238.713
	RW04	N350052.24	W0923341.65	N3500.871	W09233.694

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW04	00275	40

6
CHECKED

CITY AND STATE CONWAY, AR	ELEVATION: 276	TDZE: 276	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: CANTRELL FIELD		RNAV	RNAV (GPS) RWY 4, ORIG 13 NOVEMBER 2014	AMDT: NONE
					DATED: