

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TAA

	FROM	TO	ALT
1.	134/30 CW 314/30 (NOPT)	134/15 CW 314/15	3500
	134/15 CW 314/15	HOBUV (IF/IAF) (FB)	2600
2.	314/30 CW 134/30	314/15 CW 134/15	3500
	314/15 CW 134/15	HOBUV (IF/IAF) (FO)	2600

QUALITY
6
CHECKED

CITY AND STATE CONWAY, AR	ELEVATION: 276	TDZE: 276	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 13 NOVEMBER 2014	SUP:
	AIRPORT NAME: CANTRELL FIELD				AMDT: NONE
					DATED:

RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATIONDATA FIELDDATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KCXW
RUNWAY RW22
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR 0
REFERENCE PATH DATA SELECTOR W22A
REFERENCE PATH IDENTIFIER (APPROACH ID) 350130.8810N
LTP/FTP LATITUDE 0923255.1030W
LTP/FTP LONGITUDE +00562
LTP/FTP ELLIPSOIDAL HEIGHT 350027.4950N
FPAP LATITUDE 0923411.4650W
FPAP LONGITUDE 00040.0
THRESHOLD CROSSING HEIGHT (TCH) F
TCH UNITS SELECTOR (METERS OR FEET USED) 03.00
GLIDEPATH ANGLE (GPA) 106.75
COURSE WIDTH AT THRESHOLD 1072
LENGTH OFFSET 40.0
HORIZONTAL ALERT LIMIT (HAL) 50.0
VERTICAL ALERT LIMIT (VAL)

CRC REMAINDER

2BE49CF9

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K4
LTP ORTHOMETRIC HEIGHT +00841
FPAP ORTHOMETRIC HEIGHT +00841

QUALITY
6
CHECKED

CITY AND STATE CONWAY, AR	ELEVATION: 276 AIRPORT NAME: CANTRELL FIELD	TDZE: 276 FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 22, ORIG 13 NOVEMBER 2014	SUP:
				AMDT: NONE
				DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KCXWK4FR22	AHOBV	010HOBVVK4EA0EE	AR	HF		22380040	+	02600	18000		A	JS
SUSAP	KCXWK4FR22	R	010HOBVVK4EA0E	I	IF			+	02600	18000		A	JS
SUSAP	KCXWK4FR22	R	020ZISOLK4EA1E	F	051TF		22380060	+	01900			A	JS
SUSAP	KCXWK4FR22	R	020ZISOLK4EA2WALPV			ALNAV/VNAV						JS	
SUSAP	KCXWK4FR22	R	021OGAMEK4EA0E	S	031TF		22380026	V	0108001080		-300	A	JS
SUSAP	KCXWK4FR22	R	030RW22	K4PGOGY	M	031TF	22380024		00316		-300	A	JS
SUSAP	KCXWK4FR22	R	040		0	M	2238	+	00533			A	JS
SUSAP	KCXWK4FR22	R	050VAKUYK4EA0EY		DF			+	03000			A	JS
SUSAP	KCXWK4FR22	R	060VAKUYK4EA0EE	R	HM		04660040	+	03000			A	JS

[illegible]

QUALITY
6
CHECKED

FAA FORM 8260 - 10 / April 2006 (Computer Generated)

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
	HOBUV	HOBUV	010	IAF	HF	R	FO		223.8 (224.8T)	004.0	AA 02600	
		HOBUV	010	FACF	IF		FB				AA 02600	
		ZISOL	020	FAF	TF		FB	0.5	223.8 (224.8T)	006.0	AA 01900	
		OGAME	021	SDF	TF		FB	0.3	223.8 (224.8T)	002.6	AA 01080	GS 01080
		RW22	030	MAP	TF		FO	0.3	223.8 (224.8T)	002.4	AT 00316	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG(TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		223.8 (224.8T)		AA 00533	
	VAKUY	050		DF		FO				AA 03000	
	VAKUY	060		HM	R	FO		046.6 (047.6T)	004.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	HOBUV	N350918.88	W0922329.78	N3509.315	W09223.496
	OGAME	N350313.30	W0923051.62	N3503.222	W09230.860
	VAKUY	N345301.21	W0924406.41	N3453.020	W09244.107
	ZISOL	N350503.10	W0922839.09	N3505.052	W09228.652
	RW22	N350130.88	W0923255.10	N3501.515	W09232.918

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW22	00276	40



CITY AND STATE CONWAY, AR	ELEVATION: 276	TDZE: 276	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: CANTRELL FIELD		RNAV	RNAV (GPS) RWY 22, ORIG 13 NOVEMBER 2014	AMDT: NONE
					DATED: