U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

City, State

Airport

CONWAY, AR

CANTRELL FIELD

Effective DateAmdt. No.13 NOVEMBER 2014ORIG

TAKEOFF MINIMUMS:

RWY 04 STANDARD.

RWY 22 STANDARD WITH MINIMUM CLIMB OF 250 FT PER NM TO 680 FT.

TEXTUAL DEPARTURE PROCEDURES:

RWY 22 - CLIMBING RIGHT TURN HEADING 260 TO 1300 BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

CONTROLLING OBSTACLES:

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT: RWY 22 - 1021 FT MSL AAO 345811.01N/0923640.39W.



U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.

City, State	Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Airport Effective Date		Amdt. No.
CONWAY, AR	CANTRELL FIELD	13 NOVEMBER 2014	ORIG

05/20/2014

REMARKS:

FLIGHT INSPECTED BY: Kenneth Jack

DEVELOPED BY; ANKUR VERMA

APPROVED BY:

GEORGE GONZALEZ

- AJV-353 DR

AUG 1 1 2014

ROUTINE

REQUIRED EFFECTIVE DATE:

8/10/2014

COORDINATED WITH:

ZME ARTCC, LIT APP CON, ALPA, AOPA, NBAA, AMGR

CHANGES:

ORIGINAL

REASONS:

