



U.S. Department
of Transportation
Federal Aviation
Administration

DEPARTURE PROCEDURES/TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED WITH →		AAT	X	ATA	X	ALPA	X	AOPA	X	NBAA		APA	X	OTHER (Specify) <u>UT State Aero.</u>
Arpt Mgr, SLC FSDO, CDC FSS, ZDV ARTCC														

TAKEOFF MINIMUMS:

RWY 35: 800-1 or Standard with minimum climb of 350 feet per NM to 6700.

RWY 17: Standard

IFR DEPARTURE PROCEDURE:

RWY 17 turn left, RWY 35 turn right climb to 9000 via heading 090 and DVC R-223 to DVC VORTAC, then continue climb on course to MEA.

TAKEOFF OBSTACLE:

RWY 35: 6627 Tower 373947/1092711

THIS CANCELS NOTAM FDC 6/744

DEVELOPED BY				APPROVED BY			
SIGNATURE		DATE		SIGNATURE		DATE	
A. Kroeger		4/4/86		Dustin L. Sloan		6/16/86	
		SAC FIFO					
CITY AND STATE		AIRPORT		EFFECTIVE DATE		AMDT. NO.	
Blanding, UT		Blanding Municipal		Routine		1	