

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	MAP: 4.59 MILES AFTER PHURN LOM
MARGN INT/FNT VORTAC 48.47 DME	PHURN LOM	167.93 / 6.78	2200	CLIMB TO 2500 THEN CLIMBING LEFT TURN TO 4000 DIRECT PHURN LOM AND HOLD.
				ADDITIONAL FLIGHT DATA: HOLD SW, RT, 043.17 INBOUND. FAS OBST: 844 AAO 425113N/0823427W PHURN LOM TO RW04: 3.10/50. CHART CIRCLING ICON.

1. PT R SIDE OF COURSE 223.17 OUTBOUND 2200 FT WITHIN 10 MILES OF PHURN LOM (IAF)
 2. _____
 3. FAC 043.17 FAF PHURN LOM DIST FAF TO MAP 4.59 THLD 4.59
 4. MIN. ALT PHURN LOM 2200
 8. MSA FROM: PH LOM 105-325 2700, 325-105 2300

MAG VAR: 7W EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A	X								
CATEGORY =====>	A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	
S-04	1160	3/4	513	1160	3/4	513	1160	1	513	1160	1	513				
CIRCLING	1160	1	510	1160	1	510	1260	1 3/4	610	1260	2	610				

NOTES:

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE TROY ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, INCREASE S-04 AND CIRCLING CATS C AND D VISIBILITY 1/4.
 CHART NOTE: FOR INOPERATIVE MALSR, INCREASE S-4 CATS C AND D VISIBILITY TO 1 3/8 MILE.
 CHART NOTE: FOR INOPERATIVE MALSR WHEN USING TROY ALTIMETER SETTING, INCREASE S-4 CAT D VISIBILITY (SEE FORM 8260-10)

CITY AND STATE PORT HURON, MI	ELEVATION: 650 TDZE: 647 AIRPORT NAME: ST CLAIR COUNTY INTL	FACILITY IDENTIFIER: PH	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: NDB RWY 4, AMDT 5 18 SEPTEMBER 2014	SUP AMDT 4 DATE 08/25/2011
----------------------------------	---	----------------------------	--	----------------------------------

**NDB STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.27**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

TO 1 3/4 MILE.

CHART NOTE: NIGHT LANDING: RWY 10, 22, 28 NA.

CITY AND STATE
PORT HURON, MI

ELEVATION: 650 TDZE: 647
AIRPORT NAME:
ST CLAIR COUNTY INTL

FACILITY IDENTIFIER:
PH

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
NDB RWY 4, AMDT 5
18 SEPTEMBER 2014

SUP:
AMDT: 4
DATED: 08/25/2011