

U.S. DEPARTMENT of
TRANSPORTATION

DEPARTURE PROCEDURES / TAKEOFF MINIMUMS

Bearings, headings, courses and radials are magnetic. Elevations and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles, except visibilities which are in statute miles or in feet RVR.

COORDINATED

ATA
☐

AAT
☐

ALPA
☐

APA
☐

AOP
☒

NBAA
☒

OTHER (specify)
☒

ZAU, VOK APP CON, K82C APMGR

TAKEOFF MINIMUMS:

RWY 32: 400 - 1, OR STANDARD WITH MINIMUM CLIMB OF 220' PER NM TO 1400'.

RWY 14: 400 - 1, OR STANDARD WITH MINIMUM CLIMB OF 220' PER NM TO 1400'.

IFR DEPARTURE PROCEDURE:

TAKEOFF OBSTACLES:

RWY 32/14: 1249 TREES 434954/900930

DEPARTURE OBSTACLES:

DEVELOPED BY

SIGNATURE:

BRADLEY W. RUSH (McCLAIN)

DATE: 08/12/96

FIFO: AVN-140

APPROVED BY

SIGNATURE:

JOSEPH E. HOONEY

D MAR 20 1997

FIFO: AVN-140

CITY AND STATE

NEW LISBON, WI

AIRPORT

MAUSTON-NEW LISBON UNION

EFFECTIVE

17 JUL 97

TL97-10

AMDT. NO.

ORIG