

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.							
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW04L					
IBEKY (IF/IAF)		GOCET (FB)		043.36 / 6.85				2000		CLIMB TO 2300 DIRECT KUREC AND HOLD.					
GOCET (FAF)		HOGTO/2.20 NM TO RW04L (FB)		043.43 / 3.70											
HOGTO/2.20 NM TO RW04L		RW04L (MAP) (FO)		043.43 / 2.20											
RW04L (MAP)		345 MSL		043.43											
345 MSL		KUREC (FO)						2300		ADDITIONAL FLIGHT DATA: HOLD NE, RT, 223.56 INBOUND. CHART FAS OBST: 366 STACK 302950N/0911035W CHART: ASR. DISTANCE TO THLD FROM 276 HAT: 0.69 NM. CHART VDP AT 1.56 MILES TO RW04L* *LNAV ONLY. WAAS CHANNEL # 81825 REFERENCE PATH ID: W04A CHART CIRCLING ICON. LTP HAE: -7.2 M					
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 0E EPOCH YEAR: 2020					
2. HOLD SW IBEKY, RT, 043.36 INBOUND, 2800 FT. IN LIEU OF PT (IAF)															
3. FAC: 043.43 FAF: GOCET DIST FAF TO MAP: 5.90 THLD: 5.90															
4. MIN. ALT: IBEKY 2800, GOCET 2000, HOGTO/2.20 NM TO RW04L 820*															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: 2000 GS ALT AT: GOCET 2000 OM: _____ MM: _____ IM: _____															
7. GS ANGLE: 3.00 TCH: 55.3 34:1 IS NOT CLEAR															
8. MSA FROM: _____															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A		STANDARD @						
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	345	7/8	276	345	7/8	276	345	7/8	276	345	7/8	276			
LNAV/VNAV DA	656	2	587	656	2	587	656	2	587	656	2	587			
LNAV MDA	620	1	551	620	1	551	620	1 5/8	551	620	1 5/8	551			
CIRCLING	620	1	550	660	1	590	780	2	710	840	2 1/2	770			
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -5C (23F) OR ABOVE 54C (130F). CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING HAMMOND ALTIMETER SETTING. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HAMMOND ALTIMETER SETTING AND INCREASE (SEE FORM 8260-10)															
CITY AND STATE BATON ROUGE, LA		ELEVATION: 70 TDZE: 69 AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN FIELD		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4L, AMDT 3, 8/20/2015				SUP: AMDT: 2A DATED 04/02/2015					

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

ALL DA 91 FEET AND ALL MDA 100 FEET; INCREASE LPV VISIBILITY 1/4 MILE ALL CATS, LNAV/VNAV VISIBILITY 1/2 MILE ALL CATS AND LNAV CAT C/D VISIBILITY 1/4 MILE, CIRCLING CAT C/D VISIBILITY 1/4 MILE.

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.

TAA	FROM	TO	ALT
1.	313/30 CW 133/30 (NOPT)	IBEKY (IF/IAF) (FB)	2800
2.	133/30 CW 313/30	IBEKY (IF/IAF) (FO)	2800

QUALITY
24
CHECKED

CITY AND STATE BATON ROUGE, LA	ELEVATION: 70 AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN FIELD	TDZE: 69 FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4L, AMDT 3, 8/20/2015	SUP:
				AMDT: 2A
				DATED: 04/02/2015

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KBTR
RUNWAY	RW04L
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W04A
LTP/FTP LATITUDE	303128.3560N
LTP/FTP LONGITUDE	0910926.7070W
LTP/FTP ELLIPSOIDAL HEIGHT	-00072
FPAP LATITUDE	303233.1640N
FPAP LONGITUDE	0910815.7225W
THRESHOLD CROSSING HEIGHT (TCH)	00055.3
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0464
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0
 <u>CRC REMAINDER</u>	 C47E2015

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00199
FPAP ORTHOMETRIC HEIGHT	+00199

QUALITY
24
CHECKED

CITY AND STATE BATON ROUGE, LA	ELEVATION: 70 AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN FIELD	TDZE: 69 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4L, AMDT 3, 8/20/2015	SUP:
				AMDT: 2A
				DATED: 04/02/2015

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP	KBTRK4FR04L	AIBEKY	010IBEKYK4EA0EE	AR	HF		04340040	+	02800	18000		A	JS
SUSAP	KBTRK4FR04L	R	010IBEKYK4EA0E	I	IF			+	02800	18000		A	JS
SUSAP	KBTRK4FR04L	R	020GOCETK4EA1E	F	051TF		04340069	+	02000			A	JS
SUSAP	KBTRK4FR04L	R	020GOCETK4EA2WALPV		ALNAV/VNAV	ALNAV						JS	
SUSAP	KBTRK4FR04L	R	021HOGTOK4EA0E	S	031TF		04340037	V	0082000832	-300		A	JS
SUSAP	KBTRK4FR04L	R	030RW04LK4PG0GY	M	031TF		04340022		00121	-300		A	JS
SUSAP	KBTRK4FR04L	R	040	0	M	CA	0434	+	00345			A	JS
SUSAP	KBTRK4FR04L	R	050KURECK4EA0EY		DF			+	02300			A	JS
SUSAP	KBTRK4FR04L	R	060KURECK4EA0EE	R	HM		22360040	+	02300			A	JS

[illegible]

QUALITY
24
CHECKED

CITY AND STATE BATON ROUGE, LA	ELEVATION: 70 TDZE: 69	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN FIELD		RNAV (GPS) RWY 4L, AMDT 3, 8/20/2015	AMDT: 2A
				DATED: 04/02/2015

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	IBEKY	IBEKY	010	IAF	HF	R	FO		043.4 (043.4T)	004.0	AA 02800	
		IBEKY	010	FACF	IF		FB				AA 02800	
		GOCET	020	FAF	TF		FB	0.5	043.4 (043.4T)	006.9	AA 02000	
		HOGTO	021	SDF	TF		FB	0.3	043.4 (043.4T)	003.7	AA 00820	GS 00832
		RW04L	030	MAP	TF		FO	0.3	043.4 (043.4T)	002.2	AT 00121	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		043.4 (043.4T)		AA 00345	
		KUREC	050		DF		FO				AA 02300	
		KUREC	060		HM	R	FO		223.6 (223.6T)	004.0	AA 02300	
POINT DATA		WAYPOINT			LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS	
		GOCET			N302710.69		W0911408.56		N3027.178		W09114.143	
		HOGTO			N302952.25		W0911111.86		N3029.871		W09111.198	
		IBEKY			N302211.31		W0911935.04		N3022.189		W09119.584	
		KUREC			N304102.48		W0905856.51		N3041.041		W09058.942	
		RW04L			N303128.36		W0910926.71		N3031.473		W09109.445	
RUNWAY DATA		RWY		THRESHOLD ELEVATION		TCH						
		RW04L		00065		55						



CITY AND STATE BATON ROUGE, LA	ELEVATION: 70	TDZE: 69	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN		RNAV	RNAV (GPS) RWY 4L, AMDT 3, 8/20/2015	AMDT: 2A
	FIELD	DATED: 04/02/2015			