

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT , HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.																				
TERMINAL ROUTES										MISSED APPROACH																				
FROM			TO			COURSE AND DISTANCE			ALTITUDE		MAP: ZASVI/LSU 9.03 DME																			
LSU VORTAC			HOGNA/LSU 14.00 DME			060.44 / 14.00			1900		CLIMB TO 2200 ON LSU VORTAC R-060 DIRECT LSU VORTAC AND HOLD.																			
WALKE INT/LSU 25.84 DME (IAF)			AROLL INT/LSU 24.32 DME (NOPT)			335.00 / 8.82 (RQR R-335) (LSU LR-066)			1900																					
AROLL INT/LSU 24.32 DME (IF)			HOGNA/LSU 14.00 DME			240.44 / 10.32 (LSU R-060)			1900																					
										ADDITIONAL FLIGHT DATA: HOLD SW, RT, 065.00 INBOUND. FAS OBST: 275 AAO 303537N/0910409W CHART 547 TOWER 303337N/0910234W. CHART: ASR. CHART VDP AT 9.83 DME DISTANCE VDP TO THLD 1.27 MILES. HOGNA TO RW22R: 3.08/55. CHART CIRCLING ICON. FAC CROSSES RWY C/L EXTENDED 3000 FROM THLD.																				
1. PT <u> R </u> SIDE OF COURSE <u> 060.44 </u> OUTBOUND <u> </u> FT WITHIN <u> 10 </u> MILES OF <u> </u> HOGNA <u> </u> (IAF)										MAG VAR: 6E EPOCH YEAR:1965																				
2. <u> </u>																														
3. FAC <u> 240.44 </u> FAF <u> HOGNA/LSU 14.00 DME </u> DIST FAF TO MAP <u> </u> THLD <u> 5.43 </u>																														
4. MIN. ALT <u> HOGNA 1900 </u>																														
8. MSA FROM: LSU VORTAC 080-260 2800, 260-080 1900																														
MINIMUMS																														
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT					ALTERNATE: N A					STANDARD @																				
CATEGORY =====>		A			B			C			D			E																
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA															
S-22R	540	5500	470	540	5500	470	540	1 3/8	470	540	1 3/8	470																		
CIRCLING	560	1	490	660	1	590	780	2	710	840	2 1/2	770																		
NOTES:																														
CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY.																														
CHART NOTE: VDP NA WITH HAMMOND ALTIMETER SETTING.																														
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HAMMOND ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, AND INCREASE S-22R CAT C/D AND CIRCLING CAT C/D VISIBILITY 1/4 MILE.																														
@ NA WHEN LOCAL WEATHER NOT AVAILABLE.																														
@ CAT D 800-2 1/2																														
QUALITY 6 CHECKED																														
																CITY AND STATE BATON ROUGE, LA			ELEVATION: 70 TDZE: 70 AIRPORT NAME: BATON ROUGE METROPOLITAN, RYAN FIELD			FACILITY IDENTIFIER: LSU			PROCEDURE NO./AMDT NO./EFFECTIVE DATE: VOR/DME RWY 22R, AMDT 9A 4 FEBRUARY 2016				SUP	
																		AMDT 9		DATE 08/20/2015										