

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
IRALE (IF/IAF)	CHAPI (FB)	353.19 / 6.00	1800	LPV: DA LNAV/VNAV: DA LNAV: RW35 CLIMB TO 1800 DIRECT KBOOS AND HOLD.
CHAPI (FAF)	RW35 (MAP) (FO)	353.19 / 4.96		
RW35 (MAP)	276 MSL	353.19		
276 MSL	KBOOS (FO)		1800	ADDITIONAL FLIGHT DATA: HOLD N, RT, 173.17 INBOUND. CHART FAS OBST: 325 REFINERY 300355N/0903521W DISTANCE TO THLD FROM 269 HAT: 0.61 NM. CHART VDP AT 1.47 MILES TO RW35* *LNAV ONLY. WAAS CHANNEL # 87111 REFERENCE PATH ID: W35A CHART: CIRCLING ICON. LTP HAE: -24.4 M

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD **S** IRALE, RT, 353.19 INBOUND, 2000 FT. IN LIEU OF PT (IAF)
3. FAC: 353.19 FAF: CHAPI DIST FAF TO MAP: 4.96 THLD: 4.96
4. MIN. ALT: **IRALE 2000, CHAPI 1800**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 1800 GS ALT AT: CHAPI 1800 OM: MM: IM:
7. GS ANGLE: 3.30 TCH: 55.0 34:1 IS NOT CLEAR
8. MSA FROM:

MAG VAR: **1W** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			STANDARD @					
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	276	7/8	269	276	7/8	269	276	7/8	269		NA				
LNAV/VNAV DA	576	1 3/4	569	576	1 3/4	569	576	1 3/4	569		NA				
LNAV MDA	580	1	573	580	1	573	580	1 5/8	573		NA				
CIRCLING	700	1	693	700	1	693	820	2 1/2	813		NA				

NOTES:
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 54C (130F). @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
 CHART NOTE: DME/DME RNP-0.3 NA. @ CAT C 900-2 1/2
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
 CHART PROFILE NOTE: VGSI AND RNAV GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
 (SEE FORM 8260-10)

CITY AND STATE RESERVE, LA	ELEVATION: 7 TDZE: 7 AIRPORT NAME: ST JOHN THE BAPTIST PARISH	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 15 OCTOBER 2015	SUP: AMDT: ORIG DATED 07/02/2009
-------------------------------	---	------------------------------	--	--

QUALITY
4
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING AND INCREASE LPV DA TO 318 FEET, LNAV/VNAV DA TO 618 FEET, AND ALL MDA TO 60 FEET; INCREASE LNAV/VNAV ALL CATS AND LNAV CAT C VISIBILITY 1/8 MILE.
CHART NOTE: BARO-VNAV AND VDP NA WITH LOUIS ARMSTRONG NEW ORLEANS INTL ALTIMETER SETTING.

TAA	FROM	TO	ALT
1.	263/30 CW 083/30 (NOPT) 263/10 CW 083/10	263/10 CW 083/10 IRALE (IF/IAF) (FB)	2100 2000
2.	083/30 CW 263/30 083/7 CW 263/7	083/7 CW 263/7 IRALE (IF/IAF) (FO)	3100 2000



CITY AND STATE RESERVE, LA	ELEVATION: 7	TDZE: 7	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
	AIRPORT NAME: ST JOHN THE BAPTIST PARISH			RNAV (GPS) RWY 35, AMDT 1	AMDT: ORIG
				15 OCTOBER 2015	DATED: 07/02/2009

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	1L0
RUNWAY	RW35
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W35A
LTP/FTP LATITUDE	300449.6365N
LTP/FTP LONGITUDE	0903454.1725W
LTP/FTP ELLIPSOIDAL HEIGHT	-00244
FPAP LATITUDE	300618.1195N
FPAP LONGITUDE	0903508.1490W
THRESHOLD CROSSING HEIGHT (TCH)	00055.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.30
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1184
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER 8DED1A14

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+00020
FPAP ORTHOMETRIC HEIGHT	+00020



CITY AND STATE RESERVE, LA	ELEVATION: 7	TDZE: 7	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 15 OCTOBER 2015	SUP:
	AIRPORT NAME: ST JOHN THE BAPTIST PARISH				AMDT: ORIG
					DATED: 07/02/2009

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 1L0

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
IRALE	010	IRALE	HF	FO		353.2			R			AA 02000		EE A
	010	IRALE	IF	FB								AA 02000		E I
	020	CHAPI	TF	FB	0.5	353.2						AA 01800		E F
	030	RW35	TF	FO	0.3	353.2		3.30				AT 00062		GY M
	040		CA	FB		353.2						AA 00276		M
	050	KBOOS	DF	FO								AA 01800		EY
	060	KBOOS	HM	FO		173.2			R			AA 01800		EE

POINTS

POINT NAME	LATITUDE	LONGITUDE
CHAPI	N295953.97	W0903407.52
IRALE	N295356.45	W0903311.21
KBOOS	N301638.30	W0903646.30

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW35	N300449.64	W0903454.17	00007	55



CITY AND STATE RESERVE, LA	ELEVATION: 7 TDZE: 7	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 35, AMDT 1 15 OCTOBER 2015	SUP:
	AIRPORT NAME: ST JOHN THE BAPTIST PARISH			AMDT: ORIG
	DATED: 07/02/2009			